THE TORO COMPANY

EXECUTIVE ORDER U-U-052-0267 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DES	SCRIPTION					
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
BRIGG	S & STRATTON CORPORATION	KBSXS.4792HH	(U-U-002-1077)	479	Gasoline			
	Attachment Be Certified	EQUIPMENT D	ESCRIPTION					
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION					
2020	L4XCOLBH	22.92	art/Vehicle					
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL						
	Canister/Other	See Attachment						
Code:- Meta	E (Venting Control Type/Tank Barrier Ty al=M Treated HDPE or PE=P Co-extrud ank Barrier Codes = M, P, C, L, N, A, O)	ed=C Selar=L Nylon=N Acetal	=A Other=O B. EVAPO	RATIVE FAMILY	2-Letter CODE (Venting Control Codes			

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day or g ROG m⁻² day or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent day-1)											
1.20 + 0.056 × Nominal Capacity (L)											
	.INE PERMEATION ROG·m ⁻² ·day ⁻¹)		ANK PERMEATION ROG·m ⁻² ·day ⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)							
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER STANDAR		CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER						
15	Q-19-003 (G-05-018), Q-19-002 (Q-14-008)		Q-19-109 (Q-08-027A)	1.4	Q-19-064 (Q-08-031)						

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this _______ day of December 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division

For CARB Use Only
Executive Order: U-U- 05 z-0267

Attachment __i __ of __/

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1.	S2.	S	3.	S4.	S5.	S6.		S 7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Case (check appro		Sales Codes (check all appropriate) Engine Class (I or II)		Fuel System (FI or CARB)	Internal	Type (e.g. Single	Nomi nal Fuel Line Leng	Fuel Line Inside Diameter (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/		
		CA Only	50- State			Total	Nominal	(m²)	Multi-layer)	th ⁽¹⁾ (mm)					Other Venting Control Executive Order
	07235		x	11	Carb	29.38	22.92	0.73	Multilayer	870	6.35	KBSXS.4792HH	Q-19-109 (Q-08- 027A)	Q-19-003 (G-05-018) Q-19-002 (Q-14-008)	Q-19-064 (Q-08-031)
	07235TC		x	11	Carb	29.38	22.92	0.73	Multilayer	870	6.35	KBSXS.4792HH	Q-19-109 (Q-08- 027A)	Q-19-003 (G-05-018) Q-19-002 (Q-14-008)	Q-19-064 (Q-08-031)

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm)