## THE TORO COMPANY

EXECUTIVE ORDER U-U-052-0272
New Off-Road Small Spark-Ignition
Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DES	SCRIPTION						
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petrolet gas)				
KAWA	SAKI HEAVY INDUSTRIES, LTD	KKAXS.6032CA	(U-U-004-0771)	603	Canalina				
	KOHLER COMPANY	KKHXS.7472PF KKHXS.6942KG		747 694	Gasoline				
	Attachment Be Certified  EVAPORATIVE FAMILY	EQUIPMENT DESCRIPTION  FUEL TANK NOMINAL CAPACITY EQUIPMENT APPLICATION (liters)							
2020	L4XCOLCN	See Attachment	Other						
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
	Canister/Other	See Attachment							
Code:- Met	Canister/Other  PE (Venting Control Type/Tank Barrier Ty al=M Treated HDPE or PE=P Co-extrud Tank Barrier Codes = M, P, C, L, N, A, O)	ed=C Selar=L Nylon=N Acetal	nd Code:- Canister=C =A Other=O B. EVAPO	Sealed Tank=S( DRATIVE FAMILY	/ 2-Letter CODE (Venting Control Co				

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day or g ROG·m<sup>-2</sup>·day or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent day 1)											
		1.20 + 0.05	66 × Nominal Capacity (L)								
	INE PERMEATION ROG·m <sup>-2</sup> ·day <sup>-1</sup> )		ANK PERMEATION ROG·m <sup>-2</sup> ·day <sup>-1</sup> )	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)							
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER						
15	Q-19-003 (G-05-018), Q-19-002 (Q-14-008), Q-19-024 (C-U-05-009)		Q-19-109 (Q-08-027A)	1.4	Q-19-064 (Q-08-031), Q-19-056 (Q-09-027)						

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this

\_ day of December 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division

For CARB Use Only
Executive Order: U-U- 052 - 0272

Attachment \_\_\_\_\_ of \_\_\_t

## **Small Off-Road Evaporative Certification Database Form**

## **MODEL SUMMARY**

S1.	S2.	S	3.	S4.	<b>S</b> 5.	S6.		S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Model	Sales Codes (check all appropriate)		Engine Class (I or II)	lass System	Fuel Tank Volume (Liters)		Fuel Tank Internal Surface Area	Fuel Line Type (e.g. Single or	Nomi nal Fuel Line Lengt	Fuel Line Inside Diamete r (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA 50- Only State		Total		Nominal	(m²)	Multi-layer)	h <sup>(1)</sup> (mm)					Other Venting Control Executive Order	
	STE600CK AXXXXX		x	11	CARB	25.45	20.11	0.700	Multilayer	1319	6.35	KKAXS.6032CA	Q-19-109 (Q-08- 027A)	Q-19-003 (G-05-018) Q-19-002 (Q-14-008)	Q-19-064 (Q-08-031)
	STS650AK CXXXXX		x	. 11	FI	25.45 + 25.45	20.11 + 20.11	0.700 + 0.700	Multilayer	726 & 1463*	6.35 & 4.57*	KKHXS.6942KG	Q-19-109 (Q-08- 027A)	Q-19-003 (G-05-018) Q-19-002 (Q-14-008) Q-19-024 (C-U-05- 009) & Metal- Exempt	Q-19-056 (Q-09-027)
	STS730AK CXXXXX		х	II	FI	25.45 + 25.45	20.11 + 20.11	0.700 + 0.700	Multilayer	889 & 1463*	6.35 & 4.57*	KKHXS.7472PF	Q-19-109 (Q-08- 027A)	Q-19-003 (G-05-018) Q-19-002 (Q-14-008) Q-19-024 (C-U-05- 009) & Metal- Exempt	Q-19-056 (Q-09-027)

<sup>(1)</sup> The nominal fuel line lengths can be grouped into increment of  $\pm$  3 inches (76 mm)

(2) \* - Metal fuel line