

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION			
MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD.	LCZHS.1491H1 (U-U-082-0388)	132, 149	Gasoline
	LCZHS.1491V2 (U-U-082-0389)	132, 149	
	LCZHS.1591V2 (U-U-082-0390)	141, 159	
	LCZHS.2241V2 (U-U-082-0391)	196, 224	
TBC = To Be Certified			
EQUIPMENT DESCRIPTION			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION
2020	CZHCPXP2	See Attachment	Compressor, Edger, Logsplitter, Non-Backpack Blower, Pressure Washer, Pump, Stump Grinder, Tiller, Other
EMISSION CONTROL SYSTEMS (ECS)		ENGINE and/or EQUIPMENT MODEL	
Canister/HDPE		See Attachment	
<small>A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code:- Canister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.</small>			

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2754 or 2754.1, as applicable), and certification level in grams per day (g/day). The running loss emissions control has been demonstrated by the manufacturer.

*not applicable	DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent·day ⁻¹)		
	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL
0.95 + 0.056 × Nominal Capacity (L)	*	= (STANDARD) – (EFELD)	0.41

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.


BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 19th day of November 2019.



Allen Lyons, Chief
 Emissions Certification and Compliance Division

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1. Worst Case (Check One)	S2. Model	S3. Sales Codes (check all appropriate)		S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	S6. Fuel Tank Volume (Liters)		S7. Fuel Tank Internal Surface Area (m ²)	S8. Fuel Line Type (e.g. Single or Multi-layer)	S9. Nominal Fuel Line Length ⁽¹⁾ (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Engine Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister (or Working Capacity (g/L))/ Other Venting Control Executive Order
		CA Only	50-State			Total	Nominal								
	NH130_ NH130-01_ NH150_ NH150-01_ NH150-02_ NH150-03_ NH150-04_		X	I	CARB	1.2	1.1	0.07	Multi-layer	88	6.3	LCZHS.1491H1	N/A	N/A	2.27 g/L or 2.0 g/L
	NP130_ NP130-01_ NP150_ NP150-01_ NP150-02_ NP150-03_ NP150-04_ NP150-05_		X	I	CARB	0.85	0.75	0.05	Multi-layer	75	6.3	LCZHS.1491V2	N/A	N/A	3.33 g/L or 2.93 g/L
X	XP140_ XP140-01_ XP140-02_ XP140-03_		X	I	CARB	0.9	0.8	0.068	Multi-layer	200 or 260	6.3	LCZHS.1591V2	N/A	N/A	3.13 g/L or 2.75 g/L
	XP200-01_ XP200-02_ XP200-03_ XP200-05_ XP200-06_ XP200-07_ XP200-10_ XP225_ XP225-01_		X	I	CARB	1.4	1.3	0.08	Multi-layer	322	6.3	LCZHS.2241V2	N/A	N/A	1.92 g/L or 1.69 g/L

XP200_ XP200-08_		X	I	CARB	1.3	1.1	0.073	Multi-layer	300 or 322	6.3	LCZHS.2241V2	N/A	N/A	2.27 g/L or 2.0g/L
XP160_ XP160-01_ XP160-02_ XP160-03_ XP160-04_ XP160-05_ XP160-06_ XP160-07_		X	I	CARB	1.4	1.3	0.08	Multi-layer	300	6.3	LCZHS.1591V2	N/A	N/A	1.92 g/L or 1.69 g/L

- (1) The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm).
- (2) Postfix _ of the model name is the designator(s) for future non-emission related revision change, may appears as other number or letter.