

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION			
MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
ECI FUEL SYSTEMS	KN5XS.3042CC (U-U-008-0295) LN5XS.3042CC (U-U-008-0301)	304	Gasoline
TBC = To Be Certified			
EQUIPMENT DESCRIPTION			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION
2020	EFSCM01	See Attachments	Generator Set and Pump
EMISSION CONTROL SYSTEMS (ECS)		ENGINE and/or EQUIPMENT MODEL	
CM		See Attachments	

A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code:- Canister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2754 or 2754.1, as applicable), and certification level in g organic material hydrocarbon equivalent·day⁻¹. The running loss emissions control has been demonstrated by the manufacturer.

STANDARD	DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent·day ⁻¹)		
	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL
1.20 + 0.056 × Nominal Capacity (L)	*	= (STANDARD) - (EFELD)	0.4

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.


BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 3RD day of February 2020.


 Allen Lyons, Chief
 Emissions Certification and Compliance Division

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1. Worst Case (Check One)	S2. Model	S3. Sales Codes (check all appropriate)		S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	S6. Fuel Tank Volume (Liters)		S7. Fuel Tank Internal Surface Area (m ²)	S8. Fuel Line Type (e.g. Single or Multi-layer)	S9. Nominal Fuel Line Length ⁽¹⁾ (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Engine Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister (or Working Capacity (g/L))/ Other Venting Control Executive Order
		CA Only	50-State			Total	Nominal								
	ON7ON4.0		☐	II	CARB	26.53	23.88	0.55	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	Q-19-115
	FB10ON4.0		☐	II	CARB	38.27	34.44	0.74	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	3.56 g/L
	ON10ON4.0		☐	II	CARB	38.98	35.08	0.7	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	3.49 g/L
	ON14TON4.0		☐	II	CARB	53.09	47.78	1.16	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	2.56 g/L
	ON14bON4.0		☐	II	CARB	55.64	50.08	0.94	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	2.45 g/L
	ON14ON4.0		☐	II	CARB	55.72	50.15	0.94	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	2.44 g/L
	ON15ON4.0		☐	II	CARB	57.34	51.61	0.95	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	2.37 g/L
	ON20cON4.0		☐	II	CARB	74.3	66.87	1.29	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	1.83 g/L
	FR20ON4.0		☐	II	CARB	75.7	68.13	1.52	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	1.80 g/L
	ON20bON4.0		☐	II	CARB	75.7	68.13	1.2	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	1.80 g/L
	BIS20ON4.0		☐	II	CARB	76.65	68.99	1.75	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	1.78 g/L

For CARB Use Only
 Executive Order: U-U- 140-0083
 Attachment 2 of 2

	IND20ON4.0		□	II	CARB	76.69	69.02	1.57	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	1.78 g/L
	ON20aON4.0		□	II	CARB	76.95	69.26	1.21	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	1.77 g/L
	ON20ABON4.0		□	II	CARB	77.96	70.16	1.4	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	1.75 g/L
	VIN25ON4.0		□	II	CARB	96.23	86.61	1.73	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	1.41 g/L
	KS30ON4.0		□	II	CARB	109.77	98.79	1.96	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	2.75 g/L
	IND30ON4.0		□	II	CARB	115.03	103.53	2.12	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	2.63 g/L
□	EC40ON4.0		□	II	CARB	151.41	136.27	2.44	Multi-layer	10668.0	6.35	KN5XS.3042CC LN5XS.3042CC	N/A	Q-19-002	2.00 g/L

(1) The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)