

EXECUTIVE ORDER U-U-140-0086

New Off-Road Small Spark-Ignition
Equipment



Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DESCR	IPTION					
	MANUFACTURER	ENGINE FAMILY (E.	D. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleur gas)  Gasoline			
	ECI FUEL SYSTEMS	KHNXS.6882AA (U-UL) LHNXS.6882BA (U-U		688				
BC = To Be	Certified	EQUIPMENT DESC	RIPTION					
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION					
2020	EFSCM01H	See Attachments	Generator Set					
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL						
	СМ	See Attachments						

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2754 or 2754.1, as applicable), and certification level in g organic material hydrocarbon equivalent day<sup>-1</sup>. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	DIURNAL EMISSION STANDARD  (g organic material hydrocarbon equivalent day¹)								
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL						
1.20 + 0.056 × Nominal Capacity (L)	*	= (STANDARD) - (EFELD)	1.4						

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 3k9 day of February 2020.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 

## **Small Off-Road Evaporative Certification Database Form**

## MODEL SUMMARY

S1.	S2.	S	3.	S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Model	(chec	Sales Codes (check all appropriate)	1	Fuel System (FI or CARB)	(Liters) Interr Surfa		Fuel Tank Internal Surface Area (m²)	Internal Line Surface Type	Nominal Fuel Line Length <sup>(1)</sup> (mm)	Fuel Line Inside Diameter (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA Only	50- State			Total	Nominal		or Multi- layer)	,,,,,					Other Venting Control Executive Order
	HN630.2G		1	11	CARB	7.07	6.71	.274	Multi- layer	1828.80	6.35	LHNXS.6882BA KHNXS.6882AA	N/A	Q-19-002	Q-19-115
	HN630.3G		1	11	CARB	10.59	10.06	.301	Multi- layer	1828.80	6.35	LHNXS.6882BA KHNXS.6882AA	N/A	Q-19-002	Q-19-115
	HN630.4G		1	11	CARB	14.15	13.44	.356	Multi- layer	1828.80	6.35	LHNXS.6882BA KHNXS.6882AA	N/A	Q-19-002	Q-19-115
	HN630.7G		1	п	CARB	26.53	23.88	.55	Multi- layer	1828.80	6.35	LHNXS.6882BA KHNXS.6882AA	N/A	Q-19-002	Q-19-115
	HN630.8G		1	11	CARB	30.87	27.78	.74	Multi- layer	10058.4	6.35	LHNXS.6882BA KHNXS.6882AA	N/A	Q-19-002	Q-19-115
	HN630.14G		1	11	CARB	55.64	50.07	.94	Multi- layer	10058.4	6.35	LHNXS.6882BA KHNXS.6882AA	N/A	Q-19-002	2.45 g/L
1	HN630.20G		1	11	CARB	74.3	66.87	1.29	Multi- layer	1828.80	6.35	LHNXS.6882BA KHNXS.6882AA	N/A	Q-19-002	1.83 g/L

<sup>(1)</sup> The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)