Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION												
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)							
L	ONCIN MOTOR CO., LTD.	LCGPS.4202GR	(U-U-145-0413)	389, 420	Gasoline							
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION												
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION									
2020	CGPCM420R	See Attachment	Lawn and	I Garden Trac	npressor, Edger, Generator Set, n Tractor, Leaf Blower/Vacuum, e Washer, Pump, Tiller							
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL										
	Canister/Metal	See Attachment										
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u> :- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and</u> <u>Code</u> :- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). <u>Note</u> : Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.												

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day⁻¹ or g ROG·m⁻²·day⁻¹ or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent day ¹)												
1.20 + 0.056 × Nominal Capacity (L)												
	INE PERMEATION ROG·m⁻²·day⁻¹)		ANK PERMEATION ROG·m ⁻² ·day ⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)								
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER							
15	See Attachment	1.5	See Attachment	1.4	See Attachment							

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-145-0444-1 dated June 09, 2020.

Executed on this $\frac{31st}{2}$ day of August 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division

For CARB Use Only Executive Order: U-U-

Attachment _____ of _____

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1.	S2.	S	3.	S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14 <u>.</u>
Worst Case (Check One)	Model	(che appro	. ,	Engine Class (I or II)	Fuel System (FI or CARB)	Fuel Tank Volume (Liters)		Fuel Tank Internal Surface Area (m²)	Fuel Line Type (e.g. Single	Nominal Fuel Line Length ⁽¹⁾ (mm)	Fuel Line Inside Diameter (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA Only	50- State			Total	Nominal		or Multi- layer)						Other Venting Control Executive Order
	G390FA,G390FDA, G420FA,G420FDA, LC188F		x	Ш	CARB	6.8	5.8	0.2179	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19-023		Q-19- 093(6.28L)
	G390FA,G390FDA, G420FA,G420FDA, LC188F		x	Ш	CARB	6.5	5.7	0.220	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 093(6.28L)
	G390FA,G390FDA, G420FA,G420FDA, LC188F		x	II	CARB	30.00	30.00	0.814	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 007,Q-19- 007A,Q- 19-007B	Q-18-024 (Q-13-013) Q-19-013A (C-U-05-012)	Q-19- 099(34.0L)
	G390FA,G390FDA, G420FA,G420FDA, LC188F		x	п	CARB	32	30	0.814	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 099((34.0L)
	G390FA,G390FDA, G420FA,G420FDA, LC188F		x	II	CARB	30.50	28.00	0.729	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 007,Q-19- 007A,Q- 19-007B		Q-19- 099((34.0L)
x	G390FA,G390FDA, G420FA,G420FDA, LC188F		x	Ш	CARB	30.5	28	0.729	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A	Q-19-002 (G-05-018)	Q-19- 099((34.0L)
	G390FA,G390FDA, G420FA,G420FDA, LC188F		x	II	CARB	28.0	23.8	0.6710	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19-023		Q-19- 066(30.70L) Q-20- 032(32.5L)
	G390FA,G390FDA, G420FA,G420FDA, LC188F		x	п	CARB	28	22.5	0.712	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 066(30.70L) Q-20- 032(32.5L)
	G390FA,G390FDA, G420FA,G420FDA, LC188F		X	П	CARB	29.50	24.00	0.681	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19-062		Q-19- 066(30.70L) Q-20- 032(32.5L)

											<u>For CARB L</u> Executive C Attachment	rder: U-U-	of	
	390FA,G390FDA, 420FA,G420FDA, LC188F	х	II	CARB	29.5	24	0.681	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 066(30.70L) Q-20- 032(32.5L)
	390FA,G390FDA, 420FA,G420FDA, LC188F	X	П	CARB	34.00	32.00	0.645	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 007,Q-19- 007A,Q- 19-007B		Q-19- 099(34.0L)
	390FA,G390FDA, 420FA,G420FDA, LC188F	х	П	CARB	34	32	0.645	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 099((34.0L)
	390FA,G390FDA, 420FA,G420FDA, LC188F	x	П	CARB	30.50	28.00	0.729	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 007,Q-19- 007A,Q- 19-007B		Q-19- 099(34.0L)
	390FA,G390FDA, 420FA,G420FDA, LC188F	х	Ш	CARB	30.5	28	0.729	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 099((34.0L)
	390FA,G390FDA, 420FA,G420FDA, LC188F	x	П	CARB	34.00	32.00	0.802	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 007,Q-19- 007A,Q- 19-007B		Q-19- 099(34.0L)
G: G4	390FA,G390FDA, 420FA,G420FDA, LC188F	х	Ш	CARB	35.0	29.7	0.7071	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19-023		Q-19- 099(SINIC)(3 4.0L)
G: G4	390FA,G390FDA, 420FA,G420FDA, LC188F	х	Ш	CARB	34	32	0.802	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A	Q-18-024 (Q-13-013) Q-19-013A	Q-19- 099(SINIC)(3 4,0L)
	390FA,G390FDA, 420FA,G420FDA, LC188F	х	П	CARB	38.0	32.0	0.7551	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19-023	(C-U-05-012) Q-19-002 (G-05-018)	Q-19- 099(SINIC) Q-20- 032(32.5L)
G; G4	390FA,G390FDA, 420FA,G420FDA, LC188F	X	II	CARB	35	29.5	0.752	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 066(30.70L) Q-20- 032(32.5L)
G: G4	390FA,G390FDA, 420FA,G420FDA, LC188F	х	II	CARB	28.5	24.2	0.6570	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19-023		Q-19- 066(30.70L) Q-20- 032(32.5L)
G; G4	390FA,G390FDA, 3420FA,G420FDA, LC188F	x	П	CARB	27.5	23.5	0.682	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 066(30.70L) Q-20- 032(32.5L)
G	390FA,G390FDA, 420FA,G420FDA, LC188F	X	П	CARB	28.5	24.2	0.6570	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19-023		Q-19- 066(30.70L) Q-20- 032(32.5L)

							For CARB Use Only Executive Order: U-U- Attachment of								
G390FA,G390FDA, G420FA,G420FDA, LC188F	X	II	CARB	27	24	0.628	multilayer	<=300	4 or greater	LCGPS.4202GR	Q-19- 136A		Q-19- 066(30.70L) Q-20- 032(32.5L)		

(1) The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm)