

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DES	SCRIPTION							
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)					
Chong	gqing Rato Technology Co., Ltd.	LCRPS.0991GA LCRPS.1791GC LCRPS.2121GV LCRPS.2241GA LCRPS.2241GP	(U-U-169-0322) (U-U-169-0328) (U-U-169-0329)	99 179 212 223, 224 212, 224	Gasoline					
TBC = To B	e Certified	EQUIPMENT D	ESCRIPTION							
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION							
2020	CRPCM1R	See Attachment	Brushcutter, Chipper/Shredder, Compressor, Hedge Trimme Leaf Blower/Vacuum, Line Trimmer, Log Splitter, Non-Backpa Blower, Pressure Washer, Pump, Stump Grinder, Tiller							
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL								
	СМ	See Attachment								
Code: - Meta		ed=C Selar=L Nylon=N Acetal:	=A Other=O B. <b>EVAPO</b>	RATIVE FAMILY	Other=O 2. <u>Tank Barrier Type and</u> 2-Letter CODE (Venting Control Codes be or code. Do not use abbreviations for					

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2754 or 2754.1, as applicable), and certification level in g organic material hydrocarbon equivalent day. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent day¹)							
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL					
0.95 + 0.056 × Nominal Capacity (L)	*	= (STANDARD) - (EFELD)	0.98					

**BE IT FURTHER RESOLVED:** That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this day of February 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division

## **Small Off-Road Evaporative Certification Database Form**

## **MODEL SUMMARY**

S1.	S2.	S	3.	S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Model	Sales Codes (check all appropriate)		Engine Class (I or II)	Fuel System (FI or CARB)		nk Volume iters)	Fuel Tank Internal Surface Area (m²)	Fuel Line Type (e.g. Single	Nominal Fuel Line Length <sup>(1)</sup> (mm)	Fuel Line Inside Diameter (mm)	Engine Family	Fuel Tank Executi ve Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA Only	50- State			Total	Nominal		or Multi- layer)	,					Other Venting Control Executive Order
	R100, K100 R100-V		Х	I	CARB	1.575	1.165	0.091				LCRPS.0991GA	N/A	1	3.61
	R180-3	х	V		CARB	3.445	2.885	0.149	-			LCRPS.1791GC	N/A		1.46
	K180		^	^   '	CARB	3.925	3.325	0.17					N/A		1.26
	DO40 V	Х	V	Х	CARB	3.445	2.885	0.149				LCRPS.2121GV	N/A	Q-18-031A (Q-10-003)	1.46
	R210-V		^			3.925	3.325	0.17					N/A		1.26
			Х	I	CARB	3.445	2.885	0.149	Multi-	1050	4 or greater	4 or reater LCRPS.2241GP —	N/A	Q-18-018	1.46
X	R210P		Х	I	CARB	4.15	3.55	0.16	layer	≤350			N/A	(Q-17-043)	1.26
	R224P		Х	I	CARB	4.15	3.1	0.16					N/A	Q-19-119 (Q-15-010)	1.18
			Х	I	CARB	3.925	3.325	0.17					N/A	,	1.35
	R224 R225 R225-V		Х	I	CARB	3.445	2.885	0.149	-			LCRPS.2241GA	N/A		1.46
			Х	ı	CARB	3.925	3.325	0.17					N/A		1.26
			Х	I	CARB	4.15	3.55	0.16					N/A		1.18

<sup>(1)</sup> The nominal fuel line lengths can be grouped into increment of  $\pm$  3 inches (76 mm)