

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DES	CRIPTION							
	MANUFACTURER	ENGINE FAMILY (E.	O. NUMBER)	ENGINE SIZE	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)					
Chong	qing Rato Technology Co., Ltd.	LCRPS.2121GV (U-	U-169-0328)	212	Gasoline, Gasoline-LPG dual-fuel					
	Attachment le Certified	EQUIPMENT D	ESCRIPTION							
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)		EQUIPMENT APPLICATION						
2020	CRPCM225G	See Attachment		Compressor, Generator Set						
EMISSION	CONTROL SYSTEMS (ECS)		ENGINE and	or EQUIPMENT	MODEL					
	СМ		Se	ee Attachment						
Code:- Meta	E (Venting Control Type/Tank Barrier Ty al=M Treated HDPE or PE=P Co-extruc ank Barrier Codes = M, P, C, L, N, A, O)	ed=C Selar=L Nylon=N Acetai=	A Other=O B. EV	APORATIVE FAMILY	2-Letter CODE (Venting Control Codes					

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day or g ROG·m⁻²·day or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

	DIURNAL EMISSI	ON STANDAR	D (g organic material hydrocal	rbon equivalent d	lay1)		
		0.95 + 0.05	6 × Nominal Capacity (L)				
	INE PERMEATION ROG·m ⁻² ·day ⁻¹)		ANK PERMEATION ROG·m ⁻² ·day ⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)			
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	OR EXECUTIVE ORDE		
15	See Attachment	1.5	Q-19-132	1.4	See Attachment		

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this _____ day of February 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

For CARB Use Only
Executive Order: U-U- 169 - 0362
Attachment _ I _ of _ Z

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1.	S2.	S	33.	S4.	S5.	1	S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Model	(che	Codes ock all opriate)	Engine Class (I or II)	Fuel System (FI or CARB)		ank Volume Liters)	Fuel Tank Internal Surface Area (m²)	Fuel Line Type (e.g. Single	Nominal Fuel Line Length ⁽¹⁾ (mm)	Fuel Line Inside Diamete r (mm)	Engine Family	Fuel Tank Executiv e Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA Only	50- State			Total	Nominal	97.10	or Multi- layer)						Other Venting Control Executive Order
x	R3100P-A, R3100DP-A,		x		CARB	18.5	16	0.51	Multi-	200	4.5	1 CBBS 2424CV			Q-18-014 (C-U-07-009)
^	RP3600		^		CARB	10.5	10	0.51	layer	160	4.5	LCRPS.2121GV			Q-19-029
	R3000iSP,		x		CARB	10.5	8.5	0.32	Multi-	260	4.5	LCRPS.2121GV			Q-19-094
	R3000iEP							layer	155	4.5			Q-18-031A (Q-10-003)		
	R3500iP, R3500iDP,		х	1	CARB	8	7	0.25	Multi- layer	200	4.5	LCRPS.2121GV	Q-19-132	Q-18-018 (Q-17-043)	Q-19-029
	GN4000i		X	1	CARB	7.5	7	0.25	Multi- layer	200	4.5	LONF 3.2121GV		Q-19-119	Q-13-029
	R3000iSP-4,		х		CARB	9.5	8.5	0.35	Multi-	225	4.5	LCRPS.2121GV		(Q-15-010)	Q-19-029
	R3000iEP-4		^		CARD	9.5	0.0	0.35	layer	208	4.5	LORPS.2121GV			Q-19-029
	R3000iSP- A, R3000iEP-								Car did	310	4.5				i de la companya de l
	A, INV4000E, INV3500E, INV4000,INV3		X	6	CARB	10	8	0.33	Multi- layer	200	4.5	LCRPS.2121GV			Q-19-065 (Q-16-006)

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1.	S2.	S	3.	S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.						
Worst Case (Check One)	Model	Model		Codes ck all priate)	Engine Class (I or II)	Fuel System (FI or CARB)		nk Volume iters)	Fuel Tank Internal Surface Area (m²)	Fuel Line Type (e.g. Single	Nominal Fuel Line Length ⁽¹⁾ (mm)	Fuel Line Inside Diamete r (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/					
		CA Only	50- State			Total	Nominal		or Multi- layer)						Other Venting Control Executive Order						
	R3100DP-6, R3100P-6,					17	15	0.5	Multi-	140	4.5		Q-18-031/ (Q-10-003								
	XP4400,		X		CARB			0.0	layer	180	4.5	LCRPS.2121GV			Q-18-014 (C-U-07-009)						
	XP4400E, XP4850,XP48 50E, DS4400E				Orace	17	15	0.5	Multi- layer	120	4.5				Q-19-029						
	R3000iSP-C, R3000iEP-C	,	х		CARB	9	9 8.8 0.3		Multi- layer	260	4.5	LCRPS.2121GV			0.40.004						
					CARB			0.3		155	4.5				Q-19-094						
	R3100DPN , R3100PN	×			CARB	15	12	0.43	Multi-	340	4.5										
					CARD	В 15	12	0.43	layer	217	5.5	LCRPS.2121GV									
			Х	I	CARB	17	15	0.5	Multi- layer	310	4.5		Q-19-132	Q-18-018 (Q-17-043)	Q-19-029						
	R3100DPN- 6, R3100PN-6,												AV		A.A161	140	4.5			Q-19-119	
			X	1	CARB	17	15	0.5	Multi- layer	340	4.5			(Q-15-010)	Q-18-014						
	XP4850H,								,	180	4.5	LCRPS.2121GV			(C-U-07-009)						
	XP4850EH, XP5000RVH DS5500EH		х	1	CARB	17	15	0.5	Multi- layer	120	4.5				Q-19-029						
	R3000iEPN R3000iSPN		х		CARB	10.5	8.5	0.32	Multi-	260	4.5	LCRPS.2121GV			Q-18-014 (C-U-07-009)						
							1000000		,	155	4.5				Q-19-029						

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm).