

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION											
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
	Kohler Company	KKHXS.7252GC LKHXS.7252GD	(U-U-005-0617) (U-U-005-0655)	725	Gasoline						
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION								
2020	TRFCPAB5	20.44	CommercialTurf								
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
	Canister/HDPE		See Attachment								
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code: Carister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code: Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list verting control type or code first before tank barrier type or code. Do not use abbreviations for											

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day-1 or g ROG·m-2·day-1 or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent·day ⁻¹)										
1.20 + 0.056 × Nominal Capacity (L)										
	INE PERMEATION ROG·m ⁻² ·day ⁻¹)		ANK PERMEATION ROG·m ⁻² ·day ⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)						
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER					
15	Q-19-153 (CU-06-10)	1.5	Q-19-016	1.4	Q-19-096 (Q-09-021)					

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 2001 day of May 2020.

Allen Crans, Chief
Emissions Certification and Compliance Division

For CARB Use Only
Executive Order: U-UAttachment _____ of _____

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1.	S2.	S	3.	S4.	S5.	;	S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Model	Sales Codes (check all appropriate)		Engine Class (I or II)	Fuel System (FI or CARB)		nk Volume iters)	Fuel Tank Internal Surface Area (m²)	Fuel Line Type (e.g. Single	Nominal Fuel Line Length ⁽¹⁾ (mm)	Fuel Line Inside Diameter (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA Only	50- State			Total	Nominal		or Multi- layer)						Other Venting Control Executive Order
Х	85651CA	Х	Х	II	CARB	22.3	20.44	0.484	Multi- layer	1499	6.35	KKHXS.7252GC LKHXS.7252GD	Q-19-016	Q-19-153 (CU-06-10)	Q-19-096 (Q-09-021)

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm)