THE TORO COMPANY





Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION											
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
	KOHLER COMPANY	LKHXS.7472PF LKHXS.7252GD		747 725	Gasoline						
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION								
2021	L4XCOMBP	28.39		Riding Mower							
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
	Canister/Other	See Attachment									
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u> :- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and Code</u> :- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B, EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). <u>Note</u> : Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.											

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day or g ROG·m²-day or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent day 1)									
1.20 + 0.056 × Nominal Capacity (L)									
	INE PERMEATION ROG·m ⁻² ·day ⁻¹)		ANK PERMEATION ROG·m ⁻² ·day ⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)					
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER STANDARD CERTIFICATION LEVEL OR EXECUTIVE ORDER		CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER				
15	Q-19-003, Q-19-002, Q-19-024 1.5		Q-19-109	1.4 Q-19-064					

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 21st day of July 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1.	S2.	S	3.	S4.	S5.	S6.		S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Model	Sales (chec approp	ck all	Class Syst	Fuel System (FI or CARB)	Fuel Tank Volume (Liters)		Fuel Tank Internal Surface Area	Fuel Line Type (e.g. Single or	Nomi nal Fuel Line Leng	Fuel Line Inside Diameter (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA Only	50- State			Total	Nominal	(m ²)	Multi-layer)	th ⁽¹⁾ (mm)					Other Venting Control Executive Order
	NVS730AK CXXXXX		х	=	FI	33.89	28.39	0.777	Multilayer	1812	6.35	LKHXS.7472PF	Q-19-109	Q-19-003 Q-19-002 Q-19-024	Q-19-064
	NVS740C KCXXXXX		х	II	CARB	33.89	28.39	0.777	Multilayer	1100	6.35	LKHXS.7252GD	Q-19-109	Q-19-003 Q-19-002 Q-19-024	Q-19-064
Х	74312		Х	II	FI	33.89	28.39	0.777	Multilayer	1812	6.35	LKHXS.7472PF	Q-19-109	Q-19-003 Q-19-002 Q-19-024	Q-19-064
	74315		х	II	CARB	33.89	28.39	0.777	Multilayer	1100	6.35	LKHXS.7252GD	Q-19-109	Q-19-003 Q-19-002 Q-19-024	Q-19-064

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm)