

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DES	SCRIPTION									
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)							
KAWA	SAKI HEAVY INDUSTRIES, LTD	. LKAXS.1791CD	(U-U-004-0805)	179								
ŀ	HONDA MOTOR CO., LTD.	LHNXS.1631BZ	(U-U-001-0947)	163	Gasoline							
	KOHLER COMPANY	LKHXS.2241GD LKHXS.1731GG	(U-U-005-0640) (U-U-005-0641)	200 173								
TBC = To I	TBC = To Be Certified  EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)		EQUIPMENT	QUIPMENT APPLICATION							
2021	L4XCNMBF	See Attachment	nent Walk-Behind Mower, Other									
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL										
	Canister/Nylon See Attachment											
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code: - Canister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code: - Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.												

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2754 or 2754.1, as applicable), and certification level in g organic material hydrocarbon equivalent day. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	DIURNAL EMISSION STANDARD  (g organic material hydrocarbon equivalent day¹)									
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL							
1.0	*	= (STANDARD) – (EFELD)	0.27							

**BE IT FURTHER RESOLVED:** That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

**BE IT FURTHER RESOLVED:** That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this <u>/st</u> day of September 2020.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 

For CARB Use (	Onl <u>y</u>
<b>Executive Order</b>	:: U-U-
Attachment	of

## **Small Off-Road Evaporative Certification Database Form**

## **MODEL SUMMARY**

S1.	S2.	S	3.	S4.	S5.	S6.		S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Model	Sales (chec approp	ck all oriate)	Engine Class (I or II)	Fuel System (FI or CARB)		nk Volume iters)	Fuel Tank Internal Surface Area	Fuel Line Type (e.g. Single or	Nomi nal Fuel Line Leng	Fuel Line Inside Diameter (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA Only	50- State			Total	Nominal	(m²)	Multi-layer)	th <sup>(1)</sup> (mm)					Other Venting Control Executive Order
	ECX160C HNXXXX X		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.50	LHNXS.1631BZ	NA	G-05-018, Q-14-008, Q-07-018	1.66
	ECX180C KAXXXX X		X	I	Carb	4.24	3.76	0.188	Multi layer	318	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	ECS180CK AXXXXX		X	Ι	Carb	4.24	3.76	0.188	Multi layer	356	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	22210		X	Ι	Carb	4.24	3.76	0.188	Multi layer	356	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
X	22215		X	Ι	Carb	4.24	3.76	0.188	Multi layer	356	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	22297		X	Ι	Carb	4.24	3.76	0.188	Multi layer	318	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	22298		X	Ι	Carb	4.24	3.76	0.188	Multi layer	318	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	22295		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.50	LHNXS.1631BZ	NA	G-05-018, Q-14-008, Q-07-018	1.66
	22296		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.50	LHNXS.1631BZ	NA	G-05-018, Q-14-008, Q-07-018	1.66
	22225		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.50	LKHXS.2241GD	NA	G-05-018, Q-14-008, Q-07-018	1.66

## For CARB Use Only Executive Order: U-UAttachment \_\_\_\_\_ of \_\_\_\_

22287	X	Ι	Carb	4.24	3.76	0.188	Multi layer	260	6.35 4.50	LKHXS.1731GG	NA	G-05-018, Q-14-008, Q-07-018	1.66
ECX200C KCXXXX X	X	Ι	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.50	LKHXS.2241GD	NA	G-05-018, Q-14-008	1.66
ARS180C KAXXXX X	X	Ι	Carb	4.24	3.76	0.188	Multi layer	318	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
23515	X	Ι	Carb	4.24	3.76	0.188	Multi layer	318	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
33515	X	I	Carb	4.24	3.76	0.188	Multi layer	318	6.35	LKAXS.1791CD	NA	G-05-018, Q-14-008, Q-07-018	1.66