

MI-T-M CORPORATION

EXECUTIVE ORDER U-U-093-0054 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gauge LPG=liquefied petroleum gas)			
	LHNXS.2702BB (U-U-001-0945)	270			
HONDA MOTOR CO., LTD.	MHNXS.2702BB (U-U-001-0980)	270			
HONDA MOTOR CO., LTD.	LHNXS.3892BB (U-U-001-0944)	389			
	MHNXS 3892BB (U-U-001-0982-1)	389			
	LKHXS.2772GB (U-U-005-0665)	277]		
KOLILED COMPANY	MKHXS.2772GB (U-U-005-0690)	277	Gasoline		
KOHLER COMPANY	LKHXS.4292GB (U-U-005-0644)	429			
	MKHXS.4292GB (U-U-005-0692)	429			
CHONGQING RATO POWER	LCRPS.4202GA (U-U-169-0335)	420, 389			
MANUFACTURING CORPORATION	MCRPS.4202GA (U-U-169-0396)	420, 389			

MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION			
2021	MTMCMCL2GN	See Attachment	Generator Set			
EMISSION	I CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL				
	СМ	See Attachment				

A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code: Canister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code: Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day 1 or g ROG m⁻² day 1 or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent day¹) 1.20 + 0.056 × Nominal Capacity (L)									
FUEL LINE PERMEATION (g ROG·m²-day-1)			FANK PERMEATION ROG·m ⁻² ·day ⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)					
STANDARD	OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER				
15	See Attachment	1.5	See Attachment	1.4	See Attachment				

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.



MI-T-M CORPORATION

EXECUTIVE ORDER U-U-093-0054
New Off-Road Small Spark-Ignition
Equipment

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 7th day of March 2021.

Allen Lyons, Chief

Emissions Certification and Compliance Division

SORE Evap > 80cc Model Summary Template (rev. 2020)

Date: February 3, 2021

Evaporative Family: MTMCMCL2GN

Model Summary

For CARB Use Only Executive Order: U-U-093-0054 Attachment _1_of_1_

		Sales Code				Se Fuel Tank Vo									
S1. Worst Case (Check One)	S2. Model	appro Calif. Only	oriate) 50-State	S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	Total	Nominal	S7. Fuel Tank Internal Surface Area (m^2)	S8. Fuel Line Type (e.g. Single or Multi-Layer)	S9. Nominal Fuel Line Length (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Engine Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister (or Working Capacity (g/L)/ Other Venting Control Executive Order)
	AC-G4010H		х	П	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MHNXS.2702BB LHNXS.2702BB	Q-19-132	Q-19-153	Q-19-066
	AC-G6010H		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	AC-G6010H-E		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	AC-G7510H		х	П	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	AC-G7510H-E		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	CC-G7510H-E		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-4000-BCH0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	304.8	6.35	MHNXS.2702BB LHNXS.2702BB	Q-19-132	Q-19-153	Q-19-066
	GEN-4000-0GH0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	304.8	6.35	MHNXS.2702BB LHNXS.2702BB	Q-19-132	Q-19-153	Q-19-066
	GEN-4000-0MH0		х	П	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MHNXS.2702BB LHNXS.2702BB	Q-19-132	Q-19-153	Q-19-066
	GEN-5000-0MH0		х	П	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MHNXS.2702BB LHNXS.2702BB	Q-19-132	Q-19-153	Q-19-066
	GEN-5000-0MK0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	444.5	6.35	MKHXS.2772GB LKHXS.2772GB	Q-19-132	Q-19-153	Q-19-066
	GEN-6000-0GH0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-6000-0MH0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-6000-0MHE		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-6000-0MK0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MKHXS.4292GB LKHXS.4292GB	Q-19-132	Q-19-153	Q-19-066
	GEN-6500-HDH0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-7500-BCH0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-7500-0GHE		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-7500-0MH0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-7500-0MHE		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MHNXS.3892BB LHNXS.3892BB	Q-19-132	Q-19-153	Q-19-066
	GEN-8000-0GRE		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MCRPS.4202GA LCRPS.4202GA	Q-19-132	Q-19-153	Q-19-066
Х	GEN-8000-0MKE		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MKHXS.4292GB LKHXS.4292GB	Q-19-132	Q-19-153	Q-19-066
	GEN-8000-0MK0		х	II	CARB	27.00	25.00	0.69 m²	Multi-Layer	508	6.35	MKHXS.4292GB LKHXS.4292GB	Q-19-132	Q-19-153	Q-19-066