

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION											
	MANUFACTURER	ENGINE FAMILY (E.	O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
	KOHLER COMPANY	KKHXS.6742GC (U- KKHXS.7472PF (U- LKHXS.6742GD (U- LKHXS.7472PF (U- MKHXS.7472PF (U- MKHXS.6742GD (U-	U-005-0615) U-005-0638) U-005-0662) U-005-0682)	674, 747	Gasoline						
S.A. = See Attachment TBC = To Be Certified  EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)		ENT APPLICATION							
2021	GRCCPPNHEQ	See Attachment	Other								
EMISSION	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
	Canister/Plastic	See Attachment									
Metal=M Trea	(Venting Control Type/Tank Barrier Type ated HDPE or PE=P Co-extruded=C Sela = M, P, C, L, N, A, O). <b>Note</b> : Always list	ar=L Nylon=N Acetal=A Other=O E	EVAPORATIVE F.	AMILY 2-Letter C	ODE (Venting Control Codes =C, S, O); (Tank						

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day¹ or g ROG·m²-day¹ or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD  (g organic material hydrocarbon equivalent day 1)										
1.20 + 0.056 × Nominal Capacity (L)										
	LINE PERMEATION ROG·m <sup>-2</sup> ·day <sup>-1</sup> )		FANK PERMEATION ROG·m <sup>-2</sup> ·day <sup>-1</sup> )	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)						
STANDARD	OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER					
15	15 See Attachment		1.5 See Attachment		See Attachment					

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 30th day of April 2021.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 

Date: <u>12/08/2020</u>

Evaporative Family: \_\_GRCCPPNHEQ\_\_

Model Summary

For CARB Use Only Executive Order: U-U-196-0007 Attachment 1 of 1

			S3.				6.								
			es (Check all opriate)			Fuel Tank Vo	olume (Liters)								
S1. Worst Case (Check One)	S2. Model	Calif. Only	50-State	S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	Total	Nominal	S7. Fuel Tank Internal Surface Area (m^2)	S8. Fuel Line Type (e.g. Single or Multi-Layer)	S9. Nominal Fuel Line Length (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Engine Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister (or Working Capacity (g/L)/ Other Venting Control Executive
	25M701		Х	II	CARB	22.300	20.441	0.4840	ML	914	6.35	KKHXS.6742GC LKHXS.6742GD MKHXS.6742GD	Q-19-037	Q-19-153	Q-19-096
	25M702		х	II	CARB	22.300	20.441	0.4840	ML	914	6.35	KKHXS.6742GC LKHXS.6742GD MKHXS.6742GD	Q-19-037	Q-19-153	Q-19-096
	25M703		х	II	CARB	22.300	20.441	0.4840	ML	914	6.35	KKHXS.6742GC LKHXS.6742GD MKHXS.6742GD	Q-19-037	Q-19-153	Q-19-096
	25M704		х	II	CARB	22.300	20.441	0.4840	ML	914	6.35	KKHXS.6742GC LKHXS.6742GD MKHXS.6742GD	Q-19-037	Q-19-153	Q-19-096
	25M705		х	II	CARB	22.300	20.441	0.4840	ML	914	6.35	KKHXS.6742GC LKHXS.6742GD MKHXS.6742GD	Q-19-037	Q-19-153	Q-19-096
	25M706		х	II	CARB	22.300	20.441	0.4840	ML	914	6.35	KKHXS.7472PF LKHXS.7472PF MKHXS.7472PF	Q-19-037	Q-19-153	Q-19-096
	25M707		Х	II	CARB	22.300	20.441	0.4840	ML	914	6.35	KKHXS.7472PF LKHXS.7472PF MKHXS.7472PF	Q-19-037	Q-19-153	Q-19-096
					_										
				1											