Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION											
	MANUFACTURER	ENGINE FAMILY (E	.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
	Kohler Company	MKHXS.7472PF (U- NKHXS.7472PF (U-		725, 747	Gasoline						
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION								
2022	WLKCP2TBMF	See Attachment ZTR-Commercial, ZTR-Residential									
EMISSION	I CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
	Canister/HDPE	See Attachment									
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u> :- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and Code</u> :- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.											

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day⁻¹ or g ROG·m^{-2·}day⁻¹ or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent day ⁻¹) 1.20 + 0.056 × Nominal Capacity (L)									
	INE PERMEATION ROG·m²⋅day⁻¹)		FANK PERMEATION ⊨ROG·m ^{-2.} day ⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)					
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER				
15	15 See Attachment		See Attachment	1.4	See Attachment				

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 27th day of January 2022.

Allen Lyons, Chief Emissions Certification and Compliance Division

SORE Evap > 80cc Model Summary Template (rev. Aug. 2021)

Date: <u>December 7, 2021</u> Evaporative Family: <u>WLKCP2TBMF</u>

Model Summary

For CARB Use Only Executive Order: U-U-147-0031 Attachment _1_of_1_

		SE	8.	1		Se	5.								
S1.	S2.	Calif. Only	50-State	S4.	S5.	Total	Nominal	S7.	S8.	S9.	S10.	S11.	\$12.	S13.	S14.
Worst Case	Model			Engine Class				Fuel Tank	Fuel Line Type		Fuel Line Inside	Engine Family	Fuel Tank Executive	Fuel Line	Carbon Canister
(Check One)				(I or II)	(FI or CARB)			Internal	(e.g. Single or		Diameter (mm)	0 ,	Order	Executive Order	(or Working
(,				(,	(Surface	Multi-Layer)	(mm)					Capacity (g/L)/
								Area (m^2)		()					Other Venting
															Control Executive
															Order)
х	MH27i-2		х	П	FI	18.9, 18.9	176 176	0.465,	MULTI	2769	6.4	NKHXS.7472PF	Q-19-016	Q-19-153	Q-19-096
~	10111271-2		~	"		10.5, 10.5	17.0, 17.0	0.465	MOETT	2105	0.4	MKHXS.7472PF	Q-10-010	Q=10=100	Q-10-000
				1											
				1											
				1											
				1											