

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DES	CRIPTION								
	MANUFACTURER	ENGINE FAMILY (E.	.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
Ві	riggs & Stratton Corporation		U-U-002-1199) U-U-002-1141)	724, 810	Gasoline						
ŀ	HONDA MOTOR CO., LTD	`	J-U-001-1047) J-U-001-0993)	688							
	S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION										
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION								
2022	TRFCPAB6	See Attachment	Commercial Turf								
EMISSION	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
	СР	See Attachment									
Metal=M Trea	(Venting Control Type/Tank Barrier Type ated HDPE or PE=P Co-extruded=C Selated HDPE, N. A., O). Note : Always list	ar=L Nylon=N Acetal=A Other=O I	B. EVAPORATIVE F	AMILY 2-Letter C	ODE (Venting Control Codes =C, S, O); (Tank						

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day or g ROG·m⁻²·day⁻¹ or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent·day ⁻¹)									
1.20 + 0.056 × Nominal Capacity (L)									
	INE PERMEATION ROG·m ⁻² ·day ⁻¹)		FANK PERMEATION ROG·m ⁻² ·day⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)					
STANDARD	ANDARD CERTIFICATION LEVEL OR EXECUTIVE ORDER		CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER				
15	See Attachment	1.5	See Attachment	1.4	See Attachment				

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 18th day of December 2021.

Allen Lyons, Chief

Emissions Certification and Compliance Division

SORE Evap > 80cc Model Summary Template (rev. 2020)

Date: _10/19/2021_____
Evaporative Family: ___TRFCPAB6_____

For CARB Use Only
Executive Order: U-U-218-0039
Attachment _1__of_1__

Model Summary

		Sã)			S6	:	I		I	1		I	1	
		Sales Codes				Fuel Tank Vol									
						ruer rank voi	unie (Liters)								
S1. Worst Case (Check One)	S2. Model	approj Calif. Only	50-State	S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	Total	Nominal	S7. Fuel Tank Internal Surface Area (m^2)	S8. Fuel Line Type (e.g. Single or Multi-Layer)	S9. Nominal Fuel Line Length (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Engine Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister (or Working Capacity (g/L)/ Other Venting Control Executive Order)
	85551		Х	П	CARB	22.3	20.44	0.484	Multilayer	1016	6.35	MHNXS.6882BA NHNXS.6882BA	Q-19-016 Q-20-015	Q-19-153	Q-19-096
х	85552CA	Х		II	CARB	22.3	20.44	0.484	Multilayer	1016	6.35	MBSXS.8102VS NBSXS.8102VS	Q-19-016 Q-20-015	Q-19-153	Q-19-096
	85553CA	Х		II	CARB	22.3	20.44	0.484	Multilayer	1016	6.35	MBSXS.8102VS NBSXS.8102VS	Q-19-016 Q-20-015	Q-19-153	Q-19-096