

TEXTRON SPECIALIZED VEHICLES

EXECUTIVE ORDER U-U-260-0013New Off-Road Small Spark-Ignition
Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DE	SCRIPTION			
MANUFACTURER		ENGINE FAMILY	ENGINE FAMILY (E.O. NUMBER)		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)	
HONDA MOTOR CO., LTD.		MHNXS.6882BA	LHNXS.6882BA (U-U-001-0942) MHNXS.6882BA (U-U-001-0993) NHNXS.6882BA (U-U-001-1047)		Gasoline	
TBC = To Be	Certified	EQUIPMENT	DESCRIPTION			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION			
2023	TEXCM1	See Attachment	Other			
EMISSION	EMISSION CONTROL SYSTEMS (ECS)		ENGINE and/or EQUIPMENT MODEL			
Carbon Canister/Metal		See Attachment				
Metal=M Trea		ar=L Nylon=N Acetal=A Other=	O B. EVAPORATIVE F	AMILY 2-Letter C	er=O 2. <u>Tank Barrier Type and Code</u> :- CODE (Venting Control Codes =C, S, O); (Tank use abbreviations for ECS types.	

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2754 or 2754.1, as applicable), and certification level in g organic material hydrocarbon equivalent day. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent·day⁻¹)				
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL		
1.20 + 0.056 × Nominal Capacity (L)	*	= (STANDARD) - (EFELD)	3.65		

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 27th day of May 2022.

Films Shi for Allen Lyons, Chief

Emissions Certification and Compliance Division

SORE Evap > 80cc Model Summary Template (rev. Aug 2021)

Date: 3/23/2022

Evaporative Family: _TEXCM1_____

For CARB Use Only Executive Order: U-U-260-0013 Attachment _1_ of _1_

Model Summary

Sales Codes (Check all appropriate) Sales Codes (Check all appropr	cutive Order	S14. Carbon Canister
S1. S2. Calif. Only S0-State S4. S5. Total Nominal S7. Fuel Tank Internal Surface Area (m^2) S8. Fuel Line Length (mm) S11. S12. Fuel Tank Executive (e.g. Single or Multi-Layer) Multi-Layer (mm) S15. S8. S9. S10. S11. S12. Fuel Tank Executive (e.g. Single or Multi-Layer) Multi-Layer (mm) S15. S8. S9. S10. S10. S11. S12. S12. S13. S	Fuel Line Ca cutive Order Ca	
X Hotshot X II CARB 102.1 91.8 1.008 Multi-Layer (ID 9.5) MHNXS.6882BA N/A 9.5 LHXXS.6882BA (total combined hose lengths per		(or Working Capacity (g/L)/ Other Venting Control Executive Order)
	2-09-019A	1.4 g/L