CALIFORNIA AIR RESOURCES BOARD

ANDREAS STIHL

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION									
	MANUFACTURER	ENGINE FAMILY (I	E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)				
	ANDREAS STIHL	PA8XS.0314UA (L	PA8XS.0284UA (U-U-015-1174) PA8XS.0314UA (U-U-015-1175) PA8XS.0364UA (U-U-015-1176)		Gasoline				
TBC = To Be	TBC = To Be Certified EQUIPMENT DESCRIPTION								
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)		NT APPLICATION					
2023	PA8XS.0284EV	See Attachment	Brushcutter, Edger, Hedge Trimmer, Line Trimmer, Other						
EMISSION	I CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
	N	See Attachment							
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u> :- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and Code</u> :- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). <u>Note</u> : Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.									

The following are the evaporative emission standard (Title 13, California Code of Regulations, Section 2754 or 2754.1, as applicable), and certification level in g organic material hydrocarbon equivalent day-1.

*=not applicable	DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent⋅day⁻¹)						
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL				
0.95 + 0.056 × Nominal Capacity (L)	0.24	= (STANDARD) – (EFELD)	0.49				

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal or hot soak plus diurnal emission rate declared by the manufacturer based on evaporative emissions test results for the model of engine or equipment model within the evaporative family that is expected to exhibit the highest evaporative emission rate relative to the applicable diurnal or hot soak plus diurnal emission standard, obtained by following TP-902. No engine or equipment emissions within the evaporative family can have a diurnal emissions rate that is higher than the final declared EMEL established by final test data pursuant to TP-902.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission rate differential between the diurnal or hot soak plus diurnal emission standard in Tables 1, 2 or 3 of section 2754(a) for the model of engine or equipment within the evaporative family that is expected to exhibit the highest evaporative emission rate relative to the applicable diurnal or hot soak plus diurnal emission standard and the EMEL declared for the model and is applicable to the entire evaporative family represented by the model. The EFELD is used to determine the EO holder's compliance with the applicable diurnal emission standard, on a corporate average basis, for any equipment within this evaporative family. (See Title 13 CCR Section 2754.1(f).)

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with Title 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 8th day of May 2023.

Robin U. Lang Robin U. Lang, Chief

Emissions Certification and Compliance Division

Date:4/21/2023	
Evaporative Family: _	PA8XS.0284EV

For CARB Use Only
Executive Order: U-U-015-1224
Attachment __1__of__1__

Model Summary

		Sales (Check all a	ppropriate)	14. Fuel Tank Volume (Liters)								
11. Worst Case (Check One)	12. Model	Calif. Only	50-State	Total	Nominal	15. Fuel Tank Internal Surface Area (m^2)	16. Fuel Line Type (e.g. Single or Multi- Layer)	17. Fuel Line Length (mm)	18. Fuel Line Internal Diameter (mm)	19. Exhaust Family	20. Fuel Tank Component Executive Order	21. Fuel Line Component Executive Order
	FC 91		х	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0284UA	Q-19-129A	Q-19-139
	FC 96		х	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0284UA	Q-19-129A	Q-19-139
	FS 91		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0284UA	Q-19-129A	Q-19-139
x	FS 91 R		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0284UA	Q-19-129A	Q-19-139
	KM 91 R		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0284UA	Q-19-129A	Q-19-139
	FC 111		х	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0314UA	Q-19-129A	Q-19-139
	FS 111		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0314UA	Q-19-129A	Q-19-139
	FS 111 R		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0314UA	Q-19-129A	Q-19-139
	FS 111 R		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0314UA	Q-19-129A	Q-19-139
	KM 111 R		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0314UA	Q-19-129A	Q-19-139
	HL 111		х	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0314UA	Q-19-129A	Q-19-139
	HL 111 K		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0314UA	Q-19-129A	Q-19-139
	FB 131		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0364UA	Q-19-129A	Q-19-139
	FS 131		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0364UA	Q-19-129A	Q-19-139
	FS 131 R		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0364UA	Q-19-129A	Q-19-139
	FS 311		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0364UA	Q-19-129A	Q-19-139
	KM 131 R		x	0.73	0.71	0.054	Multi-Layer	49	3.1 ±0.25	PA8XS.0364UA	Q-19-129A	Q-19-139