



Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DE	ESCRIPTION						
	MANUFACTURER	ENGINE FAMILY	Y (E.O. NUMBER) ENGINE SIZE (cc)		FUEL TYPE (CNG/LNG=compressed/liquefied natural ga LPG=liquefied petroleum gas)				
KAWAS	SAKI HEAVY INDUSTRIES, LTD.	MKAXS.1791CD	(U-U-004-0839)	179	Gasoline				
Н	ONDA MOTOR CO., LTD.	NHNXS.1631BZ	(U-U-001-1034)	163					
	KOHLER COMPANY	NKHXS.2241GD NKHXS.1731GG		200 173					
BC = To Be	Certified	EQUIPMENT	DESCRIPTION						
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION						
2023	L4XCNPBF	See Attachment	Walk-Behind Mower, Other						
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
	Canister/Nylon	See Attachment							
Metal=M Trea	(Venting Control Type/Tank Barrier Type	ar=L Nylon=N Acetal=A Other=0	Code:- Canister=C Se	ealed Tank=S Oth	er=O 2. <u>Tank Barrier Type and Code</u> :- CODE (Venting Control Codes =C, S, O); (Tar				

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2754 or 2754.1, as applicable), and certification level in g organic material hydrocarbon equivalent day. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent day¹)							
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL					
1.0	*	= (STANDARD) - (EFELD)	0.27					

**BE IT FURTHER RESOLVED:** That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

**BE IT FURTHER RESOLVED:** That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 8th day of November 2022.

Robin U. Lang, Chief

**Emissions Certification and Compliance Division** 

Date: \_10/20/2022 \_\_ Evaporative Family: <u>L4XCNPBF</u> For CARB Use Only Executive Order: U-U-052-0334 Attachment \_1\_of\_1\_

## Model Summary

			3. s (Check all priate)				6. olume (Liters)								
S1. Worst Case (Check One)	S2. Model	Calif. Only	50-State	S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	Total	Nominal	S7. Fuel Tank Internal Surface Area (m^2)	S8. Fuel Line Type (e.g. Single or Multi-Layer)	S9. Nominal Fuel Line Length (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Engine Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister (or Working Capacity (g/L)/ Other Venting Control Executive Order)
	ECX160CHNXXXXX		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.5	NHNXS.1631BZ	NA	G-05-018, Q-14-008, Q-07-018	1.66
	ECX180CKAXXXXX		X	I	Carb	4.24	3.76	0.188	Multi layer	318	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	ECS180CKAXXXXX		X	I	Carb	4.24	3.76	0.188	Multi layer	356	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	22210		X	I	Carb	4.24	3.76	0.188	Multi layer	356	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
X	22215		X	I	Carb	4.24	3.76	0.188	Multi layer	356	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	22297		X	I	Carb	4.24	3.76	0.188	Multi layer	318	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	22298		X	I	Carb	4.24	3.76	0.188	Multi layer	318	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	22295		Х	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.5	NHNXS.1631BZ	NA	G-05-018, Q-14-008, Q-07-018	1.66
	22296		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.5	NHNXS.1631BZ	NA	G-05-018, Q-14-008, Q-07-018	1.66
	22225		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.5	NKHXS.2241GD	NA	G-05-018, Q-14-008, Q-07-018	1.66
	22235		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.5	NKHXS.2241GD	NA	G-05-018, Q-14-008, Q-07-018	1.66
	22287		X	I	Carb	4.24	3.76	0.188	Multi layer	260	6.35 4.5	NKHXS.1731GG	NA	G-05-018, Q-14-008, Q-07-018	1.66
	ECX200CKCXXXXX		X	I	Carb	4.24	3.76	0.188	Multi layer	254	6.35 4.5	NKHXS.2241GD	NA	G-05-018, Q-14-008	1.66
	ARS180CKAXXXXX		X	I	Carb	4.24	3.76	0.188	Multi layer	318	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	23515		X	I	Carb	4.24	3.76	0.188	Multi layer	318	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008	1.66
	33515	li di	X	I	Carb	4.24	3.76	0.188	Multi layer	318	6.35	MKAXS.1791CD	NA	G-05-018, Q-14-008, Q-07-018	1.66