Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION

MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
HONDA MOTOR CO., LTD.	NHNXS.2702BB (U-U-001-1051) NHNXS.3892BB (U-U-001-1045) NHNXS.6882BA (U-U-001-1047) NHNXS.7792BA (U-U-001-1029)	270, 389, 688, 779	Gasoline
BRIGGS & STRATTON LLC	NBSXS.3052HB (U-U-002-1193) NBSXS.4082HB (U-U-002-1194) NBSXS.4082HE (U-U-002-1221) NBSXS.6272HN (U-U-002-1215) NBSXS.6272HE (U-U-002-1218)	305, 408, 570, 627	Gasoline

S.A. = See Attachment
TBC = To Be Certified

EQUIPMENT DESCRIPTION

MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION
2023	WNCCM	See Attachment	Generator Set

EMISSION CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL
Canister/Metal	See Attachment

A. **ECS TYPE** (Venting Control Type/Tank Barrier Type): 1. **Venting Control Type and Code**:- Canister=C Sealed Tank=S Other=O 2. **Tank Barrier Type and Code**:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. **EVAPORATIVE FAMILY 2-Letter CODE** (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). **Note**: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent·day^{-1} or g ROG·m^{-2}·day^{-1} or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD
(g organic material hydrocarbon equivalent·day^{-1})

1.20 + 0.056 × Nominal Capacity (L)

FUEL LINE PERMEATION (g ROG·m^{-2}·day^{-1})		FUEL TANK PERMEATION (g ROG·m^{-2}·day^{-1})		CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)	
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER
15	See Attachment	1.5	See Attachment	1.4	See Attachment

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with Title 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed on this 30th day of March 2023.

Robin U. Lang

Robin U. Lang, Chief
Emissions Certification and Compliance Division

SORE Evap > 80cc Model Summary Template (rev. 2020)

For CARB Use Only
Executive Order: U-U-106-0015
Attachment _1__of_1__

Date: _3-6-2023_
Evaporative Family: _WNCCM_

Model Summary

		S3. Sales Codes (Check all appropriate)				S6. Fuel Tank Volume (Liters)									
S1. Worst Case (Check One)	S2. Model	Calif. Only	50-State	S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	Total	Nominal	S7. Fuel Tank Internal Surface Area (m^2)	S8. Fuel Line Type (e.g. Single or Multi-Layer)	S9. Nominal Fuel Line Length (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Engine Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister (or Working Capacity (g/L)/ Other Venting Control Executive Order)
	DP5000HR-03		X	II	CARB	30.2	27.18	0.71	MULTI-LAYER	609	6.35	NHNXS.2702BB	Q-22-050	Q-19-153	Q-19-115
	DP5000VR-03		X	II	CARB	30.2	27.18	0.71	MULTI-LAYER	609	6.35	NBSXS.3052HB	Q-22-050	Q-19-153	Q-19-115
X	DP7500HE-03		X	II	CARB	30.2	27.18	0.71	MULTI-LAYER	609	6.35	NHNXS.3892BB	Q-22-050	Q-19-153	Q-19-115
	DP8000VE-03		X	II	CARB	26.5	23.85	0.62	MULTI-LAYER	533.4	6.35	NBSXS.4082HB	Q-22-050	Q-19-153	Q-19-115
	W8000VE-03		X	II	CARB	26.5	23.85	0.62	MULTI-LAYER	533.4	6.35	NBSXS.4082HE	Q-19-005	Q-19-153	Q-19-115
	W1000VE-03		X	II	CARB	26.5	23.85	0.62	MULTI-LAYER	533.4	6.35	NBSXS.6272HN	Q-22-050	Q-19-153	Q-19-115
	WL12000HE-03		X	II	CARB	56.7	51.03	0.94	MULTI-LAYER	330.09	6.35	NHNXS.6882BA	Q-22-050	Q-19-153	Q-20-024
	WL12000HE-04		X	II	CARB	56.7	51.03	0.94	MULTI-LAYER	330.09	6.35	NHNXS.6882BA	Q-22-050	Q-19-153	Q-20-024
	WL12000HE-17		X	II	CARB	56.7	51.03	0.94	MULTI-LAYER	330.09	6.35	NHNXS.6882BA	Q-19-006	Q-19-153	Q-20-024
	WL12000HE-18		X	II	CARB	56.7	51.03	0.94	MULTI-LAYER	330.09	6.35	NHNXS.6882BA	Q-22-050	Q-19-153	Q-20-024
	WL16000HE-03		X	II	CARB	56.7	51.03	0.94	MULTI-LAYER	330.09	6.35	NHNXS.7792BA	Q-22-050	Q-19-153	Q-20-024
	GS12000HE		X	II	CARB	56.7	51.03	0.94	MULTI-LAYER	330.09	6.35	NHNXS.6882BA	Q-22-050	Q-19-153	Q-20-024
	HT12000HE-03		X	II	CARB	56.7	51.03	0.94	MULTI-LAYER	330.09	6.35	NHNXS.6882BA	Q-19-007	Q-19-153	Q-20-024
	DP14000VE-03		X	II	CARB	56.7	51.03	0.94	MULTI-LAYER	330.09	6.35	NBSXS.6272HN	Q-22-050	Q-19-153	Q-20-024
	WL14000VE-03		X	II	CARB	56.7	51.03	0.094	MULTI-LAYER	330.09	6.35	NBSXS.6272HE	Q-22-050	Q-19-153	Q-20-024