



Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (cc)	ENGINE CLASS	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
2006	6FJXS.7202NA	720	4-stroke, > 225 cc	CNG
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS		TYPICAL EQUIPMENT APPLICATION
500		EM		Pressure Washer, Generator and Industrial Equipment
ENGINE CODES/MODELS (rated power in kilowatt, kW)		EH72N01 (10.3 kW), EH72N02 (12.2 kW)		
<small>ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S  EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection  DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series</small>				

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission Standards and Test Procedures for 1995 and Later Small Off-Road Engines," adopted September 25, 2003.

	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	12.1	549	N/A
FAMILY EMISSION LEVEL	N/A	N/A	N/A
CERTIFICATION LEVEL	4.6	212	N/A

**BE IT FURTHER RESOLVED:** That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

**BE IT FURTHER RESOLVED:** That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

This Executive Order hereby replaces Executive Order U-U-012-0170 incorrectly dated May 19, 2006.

Executed at El Monte, California on this 31<sup>ST</sup> day of May 2005.

Allen Lyons, Chief  
Mobile Source Operations Division

Model Year: 2006  
 Manufacturer : Fuji Heavy Industries Ltd.  
 Engine Family: 6FJXS.7202NA

Issued: March 21, 2005

Page: 9

Revised:

E.O. Number U-U-012-0170-1

**CARB**

**Small Off-Road Engine Model Summary Form**

Units for Table: kW

	47. Model	48. Sales	49. Displ	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (rpm)	54. Rated Torque	55. Torque Speed (rpm)	56. Emission Control Sys.
Worst Case?	Designation	Code	(cc)							
x	EH72N01	50-State	720	84/65	26.5deg.	10.3	3600	34.0	2400	EM
	EH72N02	50-State	720	84/65	36.5deg.	12.2	3600	34.0	2400	EM
				<u>(mm)</u>	<u>(BTDC)</u>	<u>(kW)</u>		<u>(N-m)</u>		