HITACHI KOKI USA, LTD.

EXECUTIVE ORDER U-U-176-0053 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	FNGINF FAMILY		DISPLACEMENT (cc)	ENGINE CLAS	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas_LPG=liquefied petroleum gas)				
2011	B 7T 7	S.0244MP	24	2-stroke, <50	cc Gasoline				
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
300		TWC			Hedge Trimmer				
ENGINE CODES/MODELS (rated power in kilowatt, kW)			See Attachment						

ABBREVIATIONS: EM-engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC 02S=oxygen sensor H02S=heated 02S EGR=exhaust gas recirculation. AIR=secondary air injection. PAIR=pulsed AIR MFI=multi port fuel injection. SFI=sequential MFI. TBI=throttle body fuel injection. DFI=direct fue: injection. TC/SC=turbo/super charger. CAC=charge air cooler. 2(prefix)=parallel. (2)(suffix)=in series. ECM=engine control module.

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission Standards and Test Procedures for 2005 and Later Small Off-Road Engines," adopted July 26, 2004.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	50	536	2.0	
FAMILY EMISSION LEVEL	50	*	1.1	
CERTIFICATION LEVEL	45	146	0.9	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar guarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

/4_ day of April 2011.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division

Page: 9

Model Year: Manufacturer:

Engine Family:

2011

HITACHI KOKI USA LTD

B7T7S.0244MP

Issued:

Revised:

2/4/2011

u-u-176-0053

T7S.0244MP

AMACAUGUT P314 E.O. Number:

Small Off-Road Engine Model Summary Form

Units for Table: kW

	4 7.	48.	49.	50.	51.	52.	53.	54.	5 5.	56.
Worst	Model	Sales	Displ	Bore/	Ignition	Max	Rated Speed	Rated	Torque Speed	Emiss
Case?	Designation	Code	(cc)	Stroke	Timing	Power	(RPM)	Torque	(RPM)	Control Sys
×	HTS-2530PF	50-State	23.9	33/28	30 DEG	1.0	7000	0.98 N-M	5500	TWC
	HTD-2520PF	50-State	23.9	33/28	30 DEG	1.0	7000	0.98 N- M	5500	TWC
	HTD	50-State	23.9	33/28	30 EDG	1.0	7000	0.98 N-M	5500	TWC
	HTD-2526PF	50-State	23.9	33/28	30 DEG	1.0	7000	0.98 N-M	5500	TWC
	HTD	50-State	23.9	33/28	30 DEG	1.0	7000	0.98 N-M	5500	TWC
	CH50ED2	50-State	23.9	33/28	30 DEG	1.0	7000	0.98 N-M	5500	TWC
	CH55ED2	50-State	23.9	33/28	30 DEG	1.0	7000	0.98 N-M	5500	TWC
	CH66ED2	50-State	23.9	33/28	30 DEG	1.0	7000	0.98 N-M	5500	TWC
	CH78ED2	50-State	23.9	33/28	30 DEG	1.0	7000	0.98 N-M	5500	TWC