

## KOHLER COMPANY

EXECUTIVE ORDER U-U-005-0372 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
2012	СКНХ	XS.7252GB 725		4-stroke, ≥ 225 cc		Gasoline			
	DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
250	250		EM			Walk-Behind Lawnmower, Riding Mower, Tractor and Other Industrial Equipment			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							
EGR=exhaust	gas recirc	ulation AIR=seco	ondary air injection PAIR=p	oulsed AIR MFI=mu	lti port fuel injec	warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ction SFI=sequential MFI TBI=throttle body fuel injection ix)=in series ECM=engine control module			

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission Standards and Test Procedures for 2005 and Later Small Off-Road Engines," adopted July 26, 2004.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	<b>8</b> .0	549	*
FAMILY EMISSION LEVEL	7.7	549	
CERTIFICATION LEVEL	7.0	335	*

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 27 day of October 2011.

Annette Hebert, Chief

Mobile Source Operations Division

Page: 9

Model Year:

Engine Family:

2012

Manufacturer:

Kohler Co.

CKHXS.7252GB

Issued: Revised: 8/17/2011

8/17/2011

HXS.7252GB AMACHUEN PG I of [E.O. Number: U-U-005-0372]
Small Off-Road Engine Model Summary Form

Units for Table: kW

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
	SV710	50-State	725	83 x 67 mm	18°	14.94	3600	49. <b>75 N</b> -m	2200	EM
	SV715	50-State	725	83 x 67 mm	18°	14.93	3600	49. <b>8</b> 5 N-m	2200	EM
x	SV720	50-State	725	83 x 67 mm	18°	15.12	3600	50.52 N-m	2200	EM
of the grown on Advanced in Advanced Commen	SV725	50-State	725	83 x 67 mm	18°	16.24	3600	50.63 N-m	2400	EM
	SV730	50-State	725	83 x 67 mm	18°	16.40	3600	49.66 N-m	2400	EM
	SV735	50-State	725	83 x 67 mm	12-23°	17.01	3600	50.43 N-m	2600	EM
****	SV740	50-State	725	83 x 67 mm	12-23°	17.46	3600	50.69 N-m	2400	EM
	SV810	50-State	725	83 x 67 mm	18°	14.94	3600	49.75 N-m	2200	EM
	SV820	50-State	725	83 x 67 mm	18°	15.12	3600	50.52 N-m	2200	EM
1965 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975 - 1975	SV830	50-State	725	83 x 67 mm	18°	16.40	3600	49.66 N-m	2400	EM
era dell' eri eras yb il ele-	SV840	50-State	725	83 x 67 mm	12-23°	17.46	3600	50.69 N-m	2400	EM
	: :									
						1	in and a second second second second second	the first concerning to page on the con-		g shight - Make I am - Make Make I am I a
		. , , , , , , , , , , , , , , , , , , ,					· · · · · · · · · · · · · · · · · · ·		* * * * * * * * * * * * * * * * * * *	
,							The state of the s	MIN = 1 AR 1 AR 1 - W	1	•
The trees of the same		THE RESERVE AND A STATE OF THE PARTY OF THE	***************************************	o face to a series a measurement of the green				E STO MISS. I AMERICAN INCIDENCE IN MARIN.	er ter na r e marrire minimum en agres	
		(1866)   Bank   187   18   18   18   18   18   18   1	The second of th	And the second s			THE PERSON OF A PERSON OF THE			

Page: 9

Model Year:

2012

Manufacturer: Kohler Co. Issued: Revised: 8/17/2011 8/17/2011

Engine Family: CKHXS.7252GB

HXS.7252GB ATTACHUGT PG LOCIE.O. Number: U-U-005-0372

Small Off-Road Engine Model Summary Form

Units for Table: kW

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
	SV710	50-State	725	83 x 67 mm	18°	14.94	3600	49. <b>75</b> N-m	2200	EM
	SV715	50-State	725	83 x 67 mm	18°	14.93	3600	49.85 N-m	2200	EM
X	SV720	50-State	725	83 x 67 mm	18°	15.12	3600	50.52 N-m	2200	EM
	SV725	50-State	725	83 x 67 mm	18°	16.24	3600	50.63 N-m	2400	EM
A P. Commission of the St.	SV730	50-State	725	83 x 67 mm	18°	16.40	3600	49.66 N-m	2400	EM
	SV735	50-State	725	83 x 67 mm	12-23°	17.01	3600	50.43 N-m	2600	EM
	SV740	50-State	725	83 x 67 mm	12-23°	17.46	3600	50.69 N-m	2400	EM
	SV810	50-State	725	83 <b>x</b> 67 mm	18°	14.94	3600	49.75 N-m	2200	EM
	SV820	50-State	725	83 x 67 mm	18°	15.12	3600	50.52 N-m	2200	EM
	SV830	50-State	725	83 x 67 mm	18°	16.40	3600	49.66 N-m	2400	EM
	SV840	50-State	725	83 x 67 mm	12-23°	17.46	3600	50.69 N-m	2400	EM
	:					:				:
,										
			,							
	:	3								
			11.1 100 11.0 11.0 11.0 11.0 11.0 11.0		To BANKERS IN A MARK MENTINGENERAL		1		-	