EXECUTIVE ORDER U-U-017-0161-1 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGI	NE FAMILY	DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2012	CYM	(S.3572EF	357	4-stroke, ≥225 cc		Gasoline		
DURABILITY HOURS		i	SPECIAL FEATURES		TYPICAL EQUIPMENT APPLICATION			
500		EM			Compressor, Pump, Pressure Washer, Stump Beater, Generator and Non-Backpack Blower			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
EGR=exhaus	t gas recirc	ulation AIR=sec	ondary air injection PAIR=pu	ulsed AIR MFI=mu	Iti port fuel inje	warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ction SFI=sequential MFI TBI=throttle body fuel injection fix)=in series ECM=engine control module		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission"

 *=not applicable
 HC+NOx (g/kW-hr)
 CO (g/kW-hr)
 PM (g/kW-hr)

 STANDARD
 8.0
 549
 *

 FAMILY EMISSION LEVEL
 *
 *
 *

 CERTIFICATION LEVEL
 6.9
 389
 *

Standards and Test Procedures for 2005 and Later Small Off-Road Engines," adopted July 26, 2004.

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-017-0161 dated December 15, 2011.

Executed at El Monte, California on this / day of November 2012.

· . — [] []

Annette Hebert, Chief

Mobile Source Operations Division

Page: 9

Model Year:

2012

Manufacturer: YAMAHA MOTOR CO.,LTD.

Issued:

Revised: 11/16/2012

Engine Family: CYMXS.3572EF

E.O. Number: U-U-017-0(61-1

Small Off-Road Engine Model Summary Form

Units for Table: kW

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst	Model	Sales	Displ	Bore/	Ignition	Max	Rated Speed	Rated	Torque Speed	Emiss
Case?	Designation	Code	(cc)	Stroke	Timing	Power	(RPM)	Torque	(RPM)	Control Sys
Х	EF5200DE	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF5200DEQ	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF4000DQ	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF4000DEQ	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF5200DQ	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF6600D	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF6600DE	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF6600DQ	50-State	357	85x63mm	BTDC 25	7.3KW/360	3600	23.9Nm	2400	EM
	EF6600DEQ	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	7CUB-7	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	7CTB-5	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	7CTB-7	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
1 454 1 400 00000	EF4000iSE	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF4000DFW	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF6300iSDE	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	EF4000DEF	50-State	357	85x63mm	BTDC 25	7.6KW/366	3600	23.9Nm	2400	EM
	7BYB-1	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	7CUN-1	50-State	357	85x63mm	BTDC 25	7.6KW/360	3600	23.9Nm	2400	EM
	7CTJ-1	50-State	357	85x63mm	BTDC 25	7.6KW/36	3600	23.9Nm	2400	EM
	EF5200D	50-State	357	85x63mm	BTDC 25	7.6KW/36	3600	23.9Nm	2400	EM