EXECUTIVE ORDER U-U-176-0125-1 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FA		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2013	D7T7	S.0244P3	24	2-stroke, <	50 cc	Gasoline		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
300			TWC		Line Trimmer, Hedge Trimmer, Leaf Blower/Vacuum, Edger and Brushcutter			
ENGINE CODES/MODELS (rated power in kilowatt, kW)			See Attachment					
EGR=exhaus	gas recircu	ulation AIR=sec	ondary air injection PAIR=pul	sed AIR MFI=mult	i port fuel inj	=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ection SFI=sequential MFI TBI=throttle body fuel injection iffix)=in series ECM=engine control module		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission Standards and Test Procedures for 2005 and Later Small Off-Road Engines," adopted July 26, 2004.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	50	536	2.0	
FAMILY EMISSION LEVEL	49	*	0.9	
CERTIFICATION LEVEL	46	81	0.9	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-176-0125 dated December 26, 2012.

Executed at El Monte, California on this 24th day of December 2013.

Erik White, Chief

Mobile Source Operations Division

Model Year:

2013

Engine Family: D7T7S.0244P3

Manufacturer: HITACHI KOKI USA LTD

Issued:

Revised:

10/30/2013

## T7S.0244P3 AMACIMENT BJOH E.O. Number: ルールー いっし・0 (75-1) Small Off-Road Engine Model Summary Form

Units for Table: kW

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
X	TBC-260PF	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	TBC-260SF	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	TPH-260PF	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	TPE-260PF	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	TPS-260PF	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	THB-260PF	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	TBC-240PF	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	RB24E	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	CG24EKS	50-State	23.9	33X28	30 DEG	0.96	8000	0.98 N-M	5500	TWC
	TCG24EASP	50-State	23.9	33X28	30 DEG	0.85	8500	1.15 N-M	6500	TWC
	CG24EASP	50-State	23.9	33X28	30 DEG	0.85	8500	1.15 N-M	6500	TWC
	TBC-260PFL	50-State	23.9	33X28	30 DEG	0.85	8000	0.98 N-M	5500	TWC
	TBC	50-State	23.9	33X28	30 DEG	0.85	8000	0.98 N-M	5500	TWC
	TBC-240SFS	50-State	23.9	33X28	30 DEG	0.85	8000	0.98 N-M	5500	TWC
	TBC-255PF	50-State	23.9	33X28	30 DEG	0.85	8000	0.98 <b>N-M</b>	5500	TWC
	TBC-255SF	50-State	23.9	33X28	30 DEG	0.85	8000	0.98 N-M	5500	TWC
	TCG24EBSP	50-State	23.9	33X28	30 DEG	0.85	8000	0.98 N-M	5500	TWC
	TCG24EBDP	50-State	23.9	33X28	30 DEG	0.85	8000	0.98 N-M	5500	TWC