EXECUTIVE ORDER U-U-001-0657 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGI	NE FAMILY DISPLACEMENT ENGINE C		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefie petroleum gas)					
2014	EHN	(S.3892AB	389	4-stroke, ≥	225 cc	Gasoline			
DURABILITY SPECIAL FEATURES & TYPICAL EQUIPMENT APPLIC HOURS EMISSION CONTROL SYSTEMS				TYPICAL EQUIPMENT APPLICATION					
100	1000		EM		Walk-Behind Lawnmower, Riding Mower, Compressor, Pump, Generator Set, Tiller				
ENGINE CODES/MODELS (rated power in kilowatt, kW)					See Attachn	nent			
EGR=exhaus	t gas recirc	ulation AIR=seco	ondary air injection PAIR=p	oulsed AIR MFI=mu	iti port fuel inje	warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ction SFI=sequential MFI TBI=throttle body fuel injection fix)=in series ECM=engine control module			

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission Standards and Test Procedures for 2005 and Later Small Off-Road Engines," adopted July 26, 2004.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	8.0	549	*
FAMILY EMISSION LEVEL	7.8	*	*
CERTIFICATION LEVEL	6.5	389	*

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

\_\_\_ day or dand 2010

Erik White, Chief

Mobile Source Operations Division

Attachment 1 of 3

Page: 9 -1

Model Year:

2014

Manufacturer: Honda Motor Co., Ltd.

Engine Family: EHNXS.3892AB

4/24/2013

Revised:

E.O. Number: 4-4-001-0657

## Small Off-Road Engine Model Summary Form

Units for Table: kw

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated T Torque	55. orque Speed (RPM)	56. Emiss Control Sys
	E2MH01B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH0100-B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH0100R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH02B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
X	E2MH03G2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH04G2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH0500R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH0600R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH0700R	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH08B2-	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM

Attachment 2 of 3

Page: 9 -2

Model Year:

2014

Engine Family: EHNXS.3892AB

Manufacturer: Honda Motor Co., Ltd.

Issued: Revised: 4/24/2013

E.O. Number: U- U- 001 - 0657

## Small Off-Road Engine Model Summary Form

Units for Table: kw

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated T Torque	55. orque Speed (RPM)	56. Emiss Control Sys
	E2MH09B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH1000R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH1100R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH1200R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH13B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH1300~B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH1400R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH1500-B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH1500R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	E2MH16E2- C	50-State	389	88.0/64,0	10° BTDC	8.7	3600	26.5 N.m	2500	EM

Attachment 3 of 3

Page: 9 -3

Model Year:

2014

Engine Family: EHNXS.3892AB

Manufacturer: Honda Motor Co., Ltd.

0 111

Issued:

4/24/2013

Revised: E.O. Number: **u**-**u**-**001**-**065**7

## Small Off-Road Engine Model Summary Form

Units for Table: kw

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model Designation	Sales Code	Displ (cc)	Bore/ Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	Emiss Control Sys
	E2MH18B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	ΕM

