HUSQVARNA AB

EXECUTIVE ORDER U-U-019-0127 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefi petroleum gas)		
2014	EHVX	S.0254ER	25	25 2-stroke,		Gasoline		
DURABILITY HOURS			SPECIAL FEATURES &		TYPICAL EQUIPMENT APPLICATION			
300		TWC			Line Trimmer, Hedge Trimmer, Tiller, Ice Auger, Edger, Brushcutter, Other Industrial Equipment			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						

ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission Standards and Test Procedures for 2005 and Later Small Off-Road Engines," adopted July 26, 2004.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	50	536	2.0
FAMILY EMISSION LEVEL	50	500	1.0
CERTIFICATION LEVEL	37	287	0.7

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______

_ day of December 2013.

Erik White, Chief

Mobile Source Operations Division

Page: 9

Model Year:

Manufacturer:

Engine Family:

2014

Husqvarna AB

EHVXS.0254ER

Issued:

12/16/2013

Revised: 12/16/2013

E.O. Number: M-4 -019-0127

Small Off-Road Engine Model Summary Form

Units for Table: kW

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
X	327 RX/ RDX	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	(H) 327 RJX	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	(H) 326 LS	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	327 LS/LDX	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	(H) 327 PT5S	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	326 EX/327 ES	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	327 HE	50-State	24.5	34 / 27	. 28 ±2	0.82	9000	0.87 Nm	6000	TWC
	(H) 327 P	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	(H) 323 RII	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	326AI/ 327AI	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC
	(N) 159 LEB	50-State	24.5	34 / 27	28 ±2	0.82	9000	0.87 Nm	6000	TWC