EXECUTIVE ORDER U-U-001-0805 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	FNGINE FAMILY		DISPLACEMENT (cc)	(cc) ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2017			389			Gasoline		
DURABI HOUF			SPECIAL FEATURES		TYPICAL EQUIPMENT APPLICATION			
1000			EM			Walk-Behind Lawnmower, Riding Mower, Compressor, Pump, Generator Set, Tiller		
ENGINE CODES/MODELS (rated power in kilowatt, kW)			,		See Attachn	nent		
						warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ction SFI=sequential MFI TBI=throttle body fuel injection		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	8.0	549	*
FAMILY EMISSION LEVEL	7.8	*	*
CERTIFICATION LEVEL	6.5	389	*

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of October 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Attachment- Page 1 4 3 Issued: 6/21/20

Page: 9 -1

2017 Model Year:

Manufacturer: Honda Motor Co., Ltd. Engine Family: HHNXS.3892AB

Revised:

2/21/2017 E.O. Number: U-U-001-0805

Small Off-Road Engine Model Summary Form

RC1 4-20-17

Units for Table: kW

Vorst	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Forque Speed (RPM)	56. Emiss Control Sys
	H2MH01B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH0100-	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH0100R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH02B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
X	H2MH03G2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH04G2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH0500R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH0600R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH0700R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH08B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
			ŕ							

Attachment-page 2 of 3
Issued: 6/21/2016

Model Year:

Manufacturer:

2017

Engine Family: HHNXS.3892AB

Honda Motor Co., Ltd.

Revised:

E.O. Number: U-U-001-0805

Small Off-Road Engine Model Summary Form

RC1 4-20-17

Page: 9 -2

Units for Table: kw

Norst	Docionation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
	H2MH09B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	m 2500	EM
	H2MH1000R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	m 2500	EM
	H2MH1100R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	n 2500	EM
	H2MH1200R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	n 2500	EM
	H2MH13B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	n 2500	EM
	H2MH1300- B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	n 2500	EM
	H2MH1400R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	n 2500	EM
	H2MH1500- B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	m 2500	EM .
	H2MH1500R B	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	m 2500	EM
	H2MH16E2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.r	m 2500	EM

Attachment - page 3 of 3 Issued: 6/21/2016

Model Year: Manufacturer: 2017

Engine Family: HHNXS.3892AB

Honda Motor Co., Ltd.

E.O. Number: VI-U-001-0805

Small Off-Road Engine Model Summary Form

RC1 4-20-17

Units for Table: kw

Vorst	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated To Torque	55. rque Speed (RPM)	56. Emiss Control Sys
	H2MH18B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH19B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH20B2- C	50-State	389	88.0/64.0	10° BTDC	8.7	3600	26.5 N.m	2500	EM
	H2MH21B2- C	50-State	389	88.0/64.0	10° BTDC	9.0	3600	26.5 N.m	2500	EM
	H2MH22B2- C	50-State	389	88.0/64.0	10° BTDC	8.3	3600	25.0 N.m	2500	EM
										- Name
	,									