

CUMMINS POWER GENERATION

EXECUTIVE ORDER U-U-008-0290 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY DISPLACEM (cc)		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefie petroleum gas)			
2018	JN5X	(S.65321C	IC 653 4-stroke, ≥225 cc Gasoline						
DURABILITY HOURS			SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
500			TWC, PAIR		Generator Set				
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							

ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	8.0	549	*
FAMILY EMISSION LEVEL	8.0	549	*
CERTIFICATION LEVEL	4.9	361	*

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

6 day of October 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Page: 9

Model Year:

2018

Cummins Power Generation

Issued:

Revised:

8/2/2017

Manufacturer: Engine Family:

JN5XS.6532IC

E.O. Number: U- J-008 -0290

Small Off-Road Engine Model Summary Form

Units for Table: kw

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model Designation	Sales Code	Displ (cc)	Bore/ Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	Emiss Control Sys
	7HGJAA-97	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
	7HGJAD-2139	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
	7HGJAD-2141	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
X	7HGJAD-2560	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
	7HGJAD-3240	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
	7HGJAD-3252	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
	7HGJAD-3671	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
	7HGJAD-6760	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
	7HGJAD-7871	50-State	653	80/65	20	10.20	2880	33.8	2880	TWC, PAIR
	5.5HGJAA-600	50-State	653	80/65	20	8.82	2400	35.0	2400	TWC, PAIR
	5.5HGJAA-1273	50-State	653	80/65	20	8.82	2400	35.0	2400	TWC, PAIR

ATTACHMENT (page 2 of 2)

Model Year:

2018

Issued:

Manufacturer:

Cummins Power Generation Revised:

Engine Family:

JN5XS.65321C

E.O. Number U-U-008-0290

Small Off-Road Engine Model Summary Form (page 2)

	47	48	49	50	51	52	53	54	55	56
Worst	Model		Disp	Bore/S	Ignition	Max	Rated Speed	Rated	Torque Speed	Emiss Control
Case	Designation	Sales-Code	(cc)	troke	Timing	Power	(RPM)	Torque	(RPM)	Sys
	5.5HGJAD-2138	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAD-2140	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAD-2274	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAD-2558	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAD-3251	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAD-3669	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAD-6759	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAD-7860	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAD-3385	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR
	5.5HGJAA-1384	50-State	653	80/65	20	8.82	2400	35	2400	TWC,PAIR