EXECUTIVE ORDER U-U-017-0288 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGI	NE FAMILY	DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2018	JYMX	(S.3592EH	359	4-stroke, ≥225 cc		Gasoline		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
500		ЕМ			Compressor, Pump, Pressure Washer, Stump Beater, Generator, Non-Backpack Blower and Other Industrial Equipment			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
EGR=exhaus	t gas recirc	ulation AIR=sec	ondary air injection PAIR=pu	ised AIR MFI≃mu	lti port fuel inje	warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ction SFI=sequential MFI TBI=throttle body fuel injection fix)=in series ECM=engine control module		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	•	
FAMILY EMISSION LEVEL	•	*	*	
CERTIFICATION LEVEL	6.4	326	•	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of September 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Page: 9

Model Year:

2018

YAMAHA MOTOR CO.,LTD.

Issued: Revised:

10/24/2017

Manufacturer: Engine Family: JYMXS.3592EH

E.O. Number:

U-U-017-0288

Small Off-Road Engine Model Summary Form

Units for Table: kw

	47.	48.	49.	50 .	51.	52 .	53 .	54.	55.	56 .
Worst	Model	Sales	Displ	Bore/	Ignition	Max	Rated Speed	Rated	Torque Speed	Emiss
Case?	Designation	Code	(cc)	Stroke	Timing	Power	(RPM)	Torque	(RPM)	Control Sys
X	EF72DE	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	EF72DX	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	EF72DP	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	EF55DE	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	EF55DX	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	EF55DP	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	7HCB-020	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	7HDB-020	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	7HDB-030	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	7HCJ-040	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	7HDJ-030	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2400	EM
	EF55FW	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2,400	EM
	EF72E	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2,400	EM
	EF55DEX	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2,400	EM
	EF72DEX	50-State	359	85x63.2mm	BTDC 20	7.88kw	3,060	25.4Nm	2,400	EM
	7HCJ-060	50-State	359	85x63.2mm	BTDC 20	7.88kv	v 3,060	25.4Nn	n 2,400	EM