

CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD.

EXECUTIVE ORDER U-U-082-0283
New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR ENGI		NE FAMILY	DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
2018	JCZH	IS.5472V1	547	4-stroke, ≥225 cc		Gasoline			
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
250		ЕМ			Walk-Behind Lawnmower, Riding Mower, Tractor, Compressor Pump, Pressure Washer, Stump Beater, Non-Backpack Blowe Tiller, Commercial Turf, Edger, Brushcutter				
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)		
STANDARD	8.0	549	•		
FAMILY EMISSION LEVEL		*	•		
CERTIFICATION LEVEL	6.4	408	•		

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

day of January 2018.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Attachment, 1 of 1

Page: 9

Model Year:

Manufacturer:

2018

Chongqing Zongshen General Power

Revised:

9/4/2017

Engine Family: JCZHS.5472V1

E.O. Number: U - U - C82 - 0283

Small Off-Road Engine Model Summary Form

Units for Table: kw

Worst Case? Model Designation Sales Code Displementary Bore/ (cc) Ignition Timing Max Pated Speed (RPM) Rated Torque Speed (RPM) Emiss Control Sys X 4X90HU_ 4X90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 4X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 4X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90KU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM AX90HU_ 50-State 547 90/86 26 11.5 <		47.	48.	49.	50.	51.	52.	53.	54.	55.	56.	
X 4X90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 4X90KU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 4X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90KU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM AX90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM	Worst	Model	Sales	Displ	Bore/	Ignition	Max	Rated Speed	Rated	Torque Speed	Emiss	
4X90KU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 4X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90KU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM AX90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM	Case?	Designation	Code	(cc)	Stroke	Timing	Power	(RPM)	Torque	(RPM)	Control Sys	
4X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90KU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM AX90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM	X	4X90HU_	50-State	547	90/86	26	11.5	3600	34	2750	. EM	
8X90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90KU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM AX90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM		4X90KU_	50-State	547	90/86	26	11.5	3600	34	2750	EM	
8X90KU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM 8X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM AX90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM		4X90ZU_	50-State	547	90/86	26	11.5	3600	34	2750	EM	
8X90ZU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM AX90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM		8X90HU_	50-State	547	90/86	26	11.5	3600	34	2750	EM	
XP550_ 50-State 547 90/86 26 11.5 3600 34 2750 EM AX90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM		8X90KU_	50-State	547	90/86	26	11.5	3600	34	2750	EM	
AX90HU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM		8X90ZU_	50-State	547	90/86	26	11.5	3600	34	2750	EM	
-		XP550_	50-State	547	90/86	26	11.5	3600	34	2750	EM	
8X90YU_ 50-State 547 90/86 26 11.5 3600 34 2750 EM		AX90HU_	50-State	547	90/86	26	11.5	3600	34	2750	EM	
		8X90YU_	50-State	547	90/86	26	11.5	3600	34	2750	EM	