

ZHEJIANG XINGYU INDUSTRY & TRADE CO., LTD.

EXECUTIVE ORDER U-U-159-0182
New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGII	ENGINE FAMILY DISPLACEMENT (cc)		ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2018	JYKXS.2702XG		243, 270	4-stroke, ≥	225 cc	Gasoline, Gasoline/LPG Dual-Fuel		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
250		TWC, PAIR			Generator Set			
ENGINE CODES/MODELS (rated power in kilowatt, kW)					See Attach	ment		

ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)		
STANDARD	8.0	549	*		
FAMILY EMISSION LEVEL	*	*	*		
CERTIFICATION LEVEL	6.9	383	*		

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _

__ day of April 2018.

Armette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ED #U-U-159-0182

Attachment Page 1011

Page: 9

Model Year:

2018

Manufacturer: Zhejiang Xingyu Industry & Trade Co., Ltd.

Issued:

Revised:

1/23/2018

Engine Family: JYKXS.2702XG

E.O. Number:

Small Off-Road Engine Model Summary Form

Units for Table: kw

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst	Model	Sales	Displ	Bore/	Ignition	Max	Rated Speed	Rated	Torque Speed	
Case?	Designation	Code	(cc)	Stroke	Timing	Power	(RPM)	Torque	(RPM)	Control Sys
X	XG177FL II	50-State	270	77/58mm	BTDC25	4.76kW	3600	15.1N.m	2500	TWC+PAIR
	XG173FL II	50-State	243	73/58mm	BTDC25	4.45kW	3600	14.1N.m	2500	TWC+PAIR
	XG177FL	50-State	270	77/58mm	BTDC25	4.34kW	3600	15.1N.m	2500	TWC+PAIR
	XG173FL	50-State	243	73/58mm	BTDC25	4.10kW	3600	13.8N.m	2500	TWC+PAIR
	XG177F	50-State	270	77/58mm	BTDC25	4.76kW	3600	15.0N.m	2500	TWC+PAIR
	XG173F	50-State	243	73/58mm	BTDC25	4.35kW	3600	14.0N.m	2500	TWC+PAIR