

## MARUYAMA MANUFACTURING COMPANY, INC.

EXECUTIVE ORDER U-U-025-0292 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquef petroleum gas)		
2020	LM4>	(S.030415	30	2-stroke,	< 50 cc	Gasoline		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
300		EGR			Pump, Pressure Washer, Non-Backpack Blower, Backpack Blower, Line Trimmer, Hedge Trimmer, Leaf Blower/Vacuum, Edger, Brushcutter			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
EGR=exhaus	t das recirc	ulation AIR=sec	ondary air injection PAIR=r	oulsed AIR MFI=mu	iti port fuel inje	warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ction SFI=sequential MFI TBI=throttle body fuel injection ix)=in series ECM=engine control module		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	50	536	2.0	
FAMILY EMISSION LEVEL	50	*	1.0	
CERTIFICATION LEVEL	42	32	0.8	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

**BE IT FURTHER RESOLVED:** That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 57

\_\_ day of March 2020.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 

Attachment p

page

(1 of1)

Page: 9

Model Year:

2020

MARUYAMA MFG. CO., INC.

Issued: Revised: 12/12/2019 12/12/2019

Manufacturer:

Engine Family: LM4XS.030415

E.O. Number:

1.4

u-u-025-0292

## **Small Off-Road Engine Model Summary Form**

Units for Table: kW

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
X	CER300	50-State	30.1	32x28	BTDC31deg	0.97	8500	1.55Nm	6000	EGR
	CERT300	50-State	30.1	32x28	BTDC31deg	0.97	8500	1.55Nm	6000	EGR
	CER300MP	50-State	30.1	32x28	BTDC31deg	0.97	8500	1.55Nm	6000	EGR
	CER300BL	50-State	30.1	32x28	BTDC31deg	0.97	8500	1.55Nm	6000	EGR
	CER300EHT	50-State	30.1	32x28	BTDC31deg	0.97	8500	1.55Nm	6000	EGR
	CER300BP	50-State	30.1	32x28	BTDC31deg	0.97	8500	1.55Nm	6000	EGR
	CER300MD	50-State	30.1	32x28	BTDC31deg	0.97	8500	1.55Nm	6000	EGR