

CHONGQING AM PRIDE POWER & MACHINERY CO., LTD

EXECUTIVE ORDER U-U-164-0111New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)			
2020	LCPF	S.4592GC	459, 420	4-stroke, ≥	225cc	Gasoline, Gasoline-LPG dual-fuel			
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
500		EM			Compressor, Pump, Pressure Washer, Generator Set				
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment							
	gas recirc	ulation AIR=secon	ndary airinjection PAİR=po	uised AIR MF!=mul	i port fuel injecti	arm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S ion SFI=sequential MFI TBI=throttle body fuel injection c)=in series ECM=engine control module			

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	*	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	5.5	224		

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this 28th day of June 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Page: 9

Model Year: 2020

Manufacturer: CHONGQING AM PRIDE Revised: 4/2/2020

Engine Family: LCPPS.4592GC E.O. Number:

Small Off-Road Engine Model Summary Form

Issued:

Units for Table: kW

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
	AP192FB	50-State	459	92/69	25BTDC	9.5	3600	29N.m	2500	EM
X	SC460	50-State	459	92/69	25BTDC	9.5	3600	29N.m	2500	EM
	AP192FBL	50-State	459	92/69	25BTDC	9.5	3600	29N.m	2500	EM
	SC460L	50-State	459	92/69	25BTDC	9.5	3600	29N.m	2500	EM
	AP190FL	50-State	420	90/66	21BTDC	8.0	3600	24.5N.m	2500	EM
	SC420L	50-State	420	90/66	21BTDC	8.0	3600	24.5N.m	2500	EM
	SV460	50-State	459	92/69	25±2BTDC	9.4	3600	30.5N.m	2500	EM
	SC460L	50-State	459	92/69	25±2BTDC	9.4	3600	30.5N.m	2500	EM
	SV420L	50-State	420	90/66	21±3BTDC	7.9	3600	26N.m	2500	EM