

CHONGQING MAIFENG POWER **MACHINERY CO., LTD**

EXECUTIVE ORDER U-U-165-0104 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefie petroleum gas)		
2020	LCMG	S.2231GA	196, 208, 212, 223	4-stroke, >80 c	c - <225 cc	Gasoline		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
125			TWC, PAIR		Pump, Pressure Washer, Generator Set, Tiller			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
EGR=exhaus	t gas recirc	ulation AIR=seco	ondary air injection PAIR=	pulsed AIR MF1=mu	ti port fuel injec	warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S tion SFI=sequential MFI TBI=throttle body fuel injection x)=in series ECM=engine control module		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	10.0	549	*	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	6.6	374	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Emissions Certification and Compliance Division

Model Year: 2020 Issued:

Manufacturer: Chongqing Maifeng Power Machinery CO. Revised: 2/25/2020

Engine Family: LCMGS.2231GA E.O. Number:

Small Off-Road Engine Model Summary Form

Units for Table: kW

Worst	47. Model	48. Sales	49. Displ	50. Bore/	51. Ignition	52. Max	53. Rated Speed	54. Rated	55. Torque Speed	56. I Emiss
Case?	Designation	Code	(cc)	Stroke	Timing	Power	(RPM)	Torque	(RPM)	Control Sys
	170F	50-State	208	70/54	25	4.4	3600	12	2800	TWC+PAIR
	168FB	50-State	196	68/54	25	4.0	3600	11	2800	TWC+PAIR
	MF168FB	50-State	196	68/54	25	4.0	3600	11	2800	TWC+PAIR
	MF170F	50-State	208	70/54	25	4.4	3600	12	2800	TWC+PAIR
	170FA	50-State	212	70/55	25	4.5	3600	12.5	2800	TWC+PAIR
	MF170FA	50-State	212	70/55	25	4.5	3600	12.5	2800	TWC+PAIR
X	170FA-1	50-State	223	70/58	25	4.7	3600	12.8	2800	TWC+PAIR
	MF170FA-1	50-State	223	70/58	25	4.7	3600	12.8	2800	TWC+PAIR