

CHONGQING DINKING POWER MACHINERY CO., LTD

EXECUTIVE ORDER U-U-210-0111

New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2020	LCHE	OS.4582EM 389, 420, 458		4-stroke, ≥ 225 cc		Gasoline		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
250		ЕМ			Compressor, Pump, Pressure Washer, Generator Set, Tiller, Other			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module								

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission"

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	*	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	6.2	402	*	

Standards and Test Procedures for 2005 and Later Small Off-Road Engines," adopted July 26, 2004.

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

day of April 2020.

Executed at El Monte, California on this

Allen Loons, Chief

Emissions Certification and Compliance Division

Model Year: 2020

Manufacturer:

Chongqing Dinking Power Machinery Co., Revised:

Engine Family: LCHDS.4582EM E.O. Number:

Small Off-Road Engine Model Summary Form

Issued:

Units for Table: kW

1/10/2020

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model Designation	Sales Code	Displ (cc)	Bore/ Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	Emiss Control Sys
	DK192F/P-1	50-State	458	92/69	25 ±2	9.6	3600	28	2600	EM
X	192F/P-1	50-State	458	92/69	25 ±2	9.6	3600	28	2600	EM
	DK192F/P-2	50-State	458	92/69	25 ±2	9.6	3600	28	2600	EM
	192F/P-2	50-State	458	92/69	25 ±2	9.6	3600	28	2600	EM
	DK460	50-State	458	92/69	25 ±2	9.6	3600	28	2600	EM
	DK192F/P-3	50-State	458	92/69	25 ±2	9.6	3600	28	2600	EM
	192F/P-3	50-State	458	92/69	25 ±2	9.6	3600	28	2600	EM
	DK190F/P	50-State	420	90/66	23	8.5	3600	24	2500	EM
	190F/P	50-State	420	90/66	23	8.5	3600	24	2500	EM
	DK420	50-State	420	90/66	23	8.5	3600	24	2500	EM
	DK188F/P	50-State	389	88/64	23	7.6	3600	23	2500	EM
	188F/P	50-State	389	88/64	23	7.6	3600	23	2500	EM
	DK390	50-State	389	88/64	23	7.6	3600	23	2500	EM