

CHONGQING DINKING POWER MACHINERY CO., LTD

EXECUTIVE ORDER U-U-210-0112
New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc) ENGINE		CLASS	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefie petroleum gas)		
2020	LCHE	S.1761EM	150, 161, 175, 176	4-stroke, >80 cc - <225 cc		Gasoline		
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
125		EM			Walk-Behind Lawnmower, Pressure Washer, Tiller			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
EGR=exhaust	gas recirci	ulation AIR=secon	ndary airinjection PAİR=po	Ised AIR MFI=mult	port fuel injecti	arm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S on SFI=sequential MFI TBI=throttle body fuel injection)=in series ECM=engine control module		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	10	549	*	
FAMILY EMISSION LEVEL	*	**	*	
CERTIFICATION LEVEL	9.4	419	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Mente, California on this 22ND day of April 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Page: 9

Model Year: 2020

Manufacturer: Chongqing Dinking Power Machinery Co.,

Engine Family: LCHDS.1761EM

Issued: Revised:

Revised: 1/16/2020 E.O. Number:

Small Off-Road Engine Model Summary Form

Units for Table: kW

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model Designation	Sales Code	Displ (cc)	Bore/ Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	l Emiss Control Sys
	DK1P65FE/P	50-State	150	65/45.2	22°±2	2.5	3600	7.8	2500	EM
	DK1P65FE/P-1	50-State	161	65/48.5	22°±2	2.7	3600	8.5	2500	EM
	1P65FE/P-1	50-State	161	65/48.5	22°±2	2.7	3600	8.5	2500	EM
	1P65FE/P-1A	50-State	161	65/48.5	22°±2	2.7	3600	8.5	2500	EM
	DK1P65FE/P-1A	50-State	161	65/48.5	22°±2	2.7	3600	8.5	2500	EM
	1P65FE/P	50-State	150	65/45.2	22°±2	2.5	3600	7.8	2500	EM
	1P65FE/P-A	50-State	150	65/45.2	22°±2	2.5	3600	7.8	2500	EM
	DK1P65FE/P-A	50-State	150	65/45.2	22°±2	2.5	3600	7.8	2500	EM
Χ	DK1P68FE/P	50-State	176	68*48.5	22°±2	2.8	3600	9.0	2500	EM
	1P68FE/P	50-State	176	68*48.5	22°±2	2.8	3600	9.0	2500	EM
	DK1P65FE/P-3	50-State	175	65*52.7	22°±2	2.8	3600	9.0	2500	EM
	1P65FE/P-3	50-State	175	65*52.7	22°±2	2.8	3600	9.0	2500	EM
	DV160	50-State	161	65/48.5	22°±2	2.7	3600	8.5	2500	EM
	DV150	50-State	150	65/45.2	22°±2	2.5	3600	7.8	2500	EM
	DV175	50-State	176	68*48.5	22°±2	2.8	3600	9.0	2500	EM