

## CHONGQING DINKING POWER MACHINERY CO., LTD

EXECUTIVE ORDER U-U-210-0115
New Off-Road Small Spark-Ignition
Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

YEAR	ODEL ENGINE FA		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2020	LCHD	S.2231EM	196, 212, 223	4-stroke, >80 d	>80 cc - <225 cc Gasoline			
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
125		EM			Compressor, Pump, Pressure Washer, Generator Set, Tiller, Other			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission Standards and Test Procedures for 2005 and Later Small Off-Road Engines," adopted July 26, 2004.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	10.0	549	*	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	7.2	371	*	

**BE IT FURTHER RESOLVED**: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

**BE IT FURTHER RESOLVED:** That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monto, California on this

Allen Lyons, Chief

Emissions Certification and Compliance Division

Model Year: 2020

Manufacturer: Chongqing Dinking Power Machinery Co., Revised: 2/6/2020

Engine Family: LCHDS.2231EM E.O. Number:

## **Small Off-Road Engine Model Summary Form**

Issued:

Units for Table: kW

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case?	Model Designation	Sales Code	Displ (cc)	Bore/ Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	I Emiss Control Sys
X	DK170F/P-1	50-State	223	70/58	<b>25</b> ±2	4.5	3600	13	2500	EM
	170F/P-1	50-State	223	70/58	<b>25</b> ±2	4.5	3600	13	2500	EM
	DK225	50-State	223	70/58	<b>25</b> ±2	4.5	3600	13	2500	EM
	DK170F/P	50-State	212	70/55	<b>25</b> ±2	4.0	3600	12	2500	EM
	170F/P	50-State	212	70/55	<b>25</b> ±2	4.0	3600	12	2500	EM
	DK210	50-State	212	70/55	<b>25</b> ±2	4.0	3600	12	2500	EM
	DK170F/P-2	50-State	212	70/55	<b>25</b> ±2	4.0	3600	12	2500	EM
	170F/P-2	50-State	212	70/55	<b>25</b> ±2	4.0	3600	12	2500	EM
	DK170FD/P-2	50-State	212	70/55	<b>25</b> ±2	4.0	3600	12	2500	EM
	170FD/P-2	50-State	212	70/55	<b>25</b> ±2	4.0	3600	12	2500	EM
	DK168F/P-1	50-State	196	68/54	<b>25</b> ±2	3.8	3600	11	2500	EM
	168F/P-1	50-State	196	68/54	<b>25</b> ±2	3.8	3600	11	2500	EM
	168F/P-1、	50-State	196	68/54	<b>25</b> ±2	3.8	3600	11	2500	EM