

BRIGGS & STRATTON, LLC

EXECUTIVE ORDER U-U-002-1139-1

New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR ENGI	I ENGINE FAMILY		ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2021 MBSXS.5402VL		540	4-stroke, > 225 cc		Gasoline		
DURABILITY HOURS		SPECIAL FEATURES		TYPICAL EQUIPMENT APPLICATION			
250		EM		Riding Mower, Tractor, Generator Set			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment					

ABBREVIATIONS: EM=engine modification in WC/OC=three-way/oxidizing catalysis WOTW/OVOC=warm-up invo/OC OZS=oxygen sensor HOZS=neated OZS EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	*	
FAMILY EMISSION LEVEL	8.3	549	*	
CERTIFICATION LEVEL	5.8	531	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby cancels and replaces Executive Order U-U-002-1139 dated December 18, 2020.

Executed on this 24th day of December 2021.

Allen Lyons, Chief

Emissions Certification and Compliance Division

SORE Exhaust Model Summary Te	mplate (rev. 2020)
-------------------------------	--------------------

Date:	_11/11/2021
Engine Family:	MBSXS.5402VL

For CARB Use Only Executive Order: U-U-002-1139-1 Attachment _1_ of _1_

Model Summary

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case (Check	Model	Sales Code	Displacement	Bore/Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	Emission Control System
One)	Designation		(cc)			(kW)				
	33R7		540	94.0 / 77.8	25	13.3	3600	40.1	2600	EM
	33S7		540	94.0 / 77.8	25	13.3	3600	40.1	2600	EM
	33R8		540	94.0 / 77.8	25	14.00	3600	39.9	2800	EM
	33S8	50-State	540	94.0 / 77.8	25	14.00	3600	39.9	2800	EM