Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR			DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2021	2021 MLCTS.4792RX		414, 420, 458, 479	4-stroke, \geq 225 cc		Gasoline		
DURABILITY HOURS			SPECIAL FEATURES & SSION CONTROL SYS1		TYPICAL EQUIPMENT APPLICATION			
250		EM			Compressor, Pump, Pressure Washer, Generator Set			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas revirculation AB=secondary air injection PAIR=rulesd AIR MEI=multi port fuel injection SEI=sequential MEI TBI=throttle body fuel injection DEI=direct fuel								

EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throt injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	*	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	7.0	506	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this <u>2nd</u> day of April 2021.

Allen Zyons, Chief Emissions Certification and Compliance Division

SORE Exhaust Model Summary Template (rev. 2020)

 Date:
 3/10/2021

 Engine Family:
 MLCTS.4792RX

Model Summary

inouci summa	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case (Check One)	Model	Sales Code	Displacement	Bore/Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque	Torque Speed (RPM)	Emission Control System
(Check One)	Designation		(cc)							
	PLMHP-E1 414	50-State	414	90 / 65	fixed	8.84	3600	23.4	3600	EM
	PLMHP-E1X 414	50-State	414	90 / 65	fixed	8.84	3600	23.4	3600	EM
	PLMHK-E1 414	50-State	414	90 / 65	fixed	8.84	3600	23.4	3600	EM
х	PLMHP-E1 420	50-State	420	90 / 66	fixed	9.12	3600	24.2	3600	EM
	PLMHK-E1 420	50-State	420	90 / 66	fixed	9.12	3600	24.2	3600	EM
	PLMHP-E1 458	50-State	458	92 / 69	fixed	9.92	3600	26.3	3600	EM
	PLMHK-E1 458	50-State	458	92 / 69	fixed	9.92	3600	26.3	3600	EM
	PLMHP-E1 479	50-State	479	94 / 69	fixed	11.25	3600	29.8	3600	EM
	PLMHK-E1 479	50-State	479	94 / 69	fixed	11.25	3600	29.8	3600	EM

For CARB Use Only Executive Order: U-U-063-0231 Attachment 1 of 1