

MTD Southwest Inc.

EXECUTIVE ORDER U-U-020-0440

New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2022	NMTE	OS.0254SL	25	2-9	stroke, < 50 cc	Gasoline		
DURABI HOU		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
50			ОС		Non-Backpack Blower,Leaf Blower/Vacuum, Tiller			
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment						
EGR=exhaus	t gas recirc	ulation AIR=seco	ndary air injection PAIR=pı	ulsed AIR N	ÁFI=multi port fuel injectio	rm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S on SFI=sequential MFI TBI=throttle body fuel injection c)=in series ECM=engine control module		

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	50	536	2.0	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	46	287	1.1	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this /4th day of November 2021.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Date: 08/14/2021

Engine Family: NMTDS.0254SL

For CARB Use Only

Executive Order: U-U-020-0440

Attachment 1 of 1

Model Summary

Model Summary										
Worst Case	47. Model	48. Sales Code	49. Displacement	50. Bore/Stroke	51. Ignition Timing	52. Max Power	52. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emission Control System
(Check One)	Designation	Jaies Code	(cc)	(mm)	igilition filling	(kW)	nateu speeu (nrwi)	nateu rorque	Torque Speed (NEW)	Linission Control system
Х	P25TR.4	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	ОС
	Black & Decker	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Bolens	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Yard Machines	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Troy-Bilt	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Remington	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Murray	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Murray Select	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Craftsman	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Craftsman Pro	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Yard-Man	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Cub Cadet	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Rover	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Snapper	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC
	Hyper Tough	50-State	25	35.0/26.0	27°BTDC	0.78	8000	1.11 Nm	6000	OC