

ZHEJIANG CONSTANT ENGINE MADING CO., LTD

EXECUTIVE ORDER U-U-243-0076 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMII	DISPLACEMENT (cc)	ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
2022	NZCES.1931G	171, 193	171, 193 4-stroke, > 80 cc - < 225 cc Gasoline, LPG, Gasoline-LPG Dua				
DURABILITY HOURS	-	SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION		
500		EM			Pump, Pressure Washer, Generator Set, Other		
ENGINE CODES/MODE (rated power kilowatt, kW	in			See Attachme	ent		

ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	10.0	549	*	
FAMILY EMISSION LEVEL	*	*	*	
CERTIFICATION LEVEL	9.7	372	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar guarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this 20th day of August 2021.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Date: _07/5/2021____ Engine Family: NZCES.1931GD

or CARB Use	Onl	У		
xecutive Ord	ler:	U-U-24	13-00	76
ttachment	1	of	1	

Model Summary

Worst Case (Check One)	47. Model Designation	48. Sales Code	49. Displacement (cc)	50. Bore/Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emission Control System
Х	CT166FD-B2	50-State	171	66/50	23±2 BTDC	3.8kW	3800	11.2Nm	2800	EM
	CT166FDE-B3	50-State	171	66/50	23±2 BTDC	3.8kW	3800	11.2Nm	2800	EM
	CT166FDE-B4	50-State	171	66/50	23±2 BTDC	3.8kW	3800	11.2Nm	2800	EM
	CT166FD-B1	50-State	171	66/50	23±2 BTDC	3.8kW	3800	11.2Nm	2800	EM
	CT166FDE-B1	50-State	171	66/50	23±2 BTDC	3.8kW	3800	11.2Nm	2800	EM
	CT166FDE-B2	50-State	171	66/50	23±2 BTDC	3.8kW	3800	11.2Nm	2800	EM
	CT170FD-B5	50-State	193	70/50	25±2 BTDC	4.2kW	3800	11.5Nm	2500	EM
	CT170FDE-B5	50-State	193	70/50	25±2 BTDC	4.2kW	3800	11.5Nm	2500	EM
	CT170FD-B2	50-State	193	70/50	25±2 BTDC	4.2kW	3800	11.5Nm	2500	EM
	CT170FDE-B3	50-State	193	70/50	25±2 BTDC	4.2kW	3800	11.5Nm	2500	EM
	CT170FDE-B4	50-State	193	70/50	25±2 BTDC	4.2kW	3800	11.5Nm	2500	EM
	CT166FD-B3	50-State	171	66/50	23±2 BTDC	3.4kW	3800	10Nm	2800	EM
	CT166FDE-B5	50-State	171	66/50	23±2 BTDC	3.4kW	3800	10Nm	2800	EM
	CT170FD-B6	50-State	193	70/50	25±2 BTDC	3.8	3800	10.3Nm	2500	EM
	CT170FDE-B6	50-State	193	70/50	25±2 BTDC	3.8	3800	10.3Nm	2500	EM