State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-290-60

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

DETROIT DIESEL CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 1997 model-year Detroit Diesel Corporation diesel-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family		Displacement (Cubic Inches)	Exhaust Emission Control Systems and Special Features
VDD3.8C8DABA	3.8	(232)	Turbocharger Charge Air Cooler Powertrain Control Module Oxidation Catalytic Converter

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>	
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>		
1.3	15.5	5.0	0.10	

The following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
0.1	0.4	3.7	0.09

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

R. B. Summerfield, Chief

Mobile Source Operations Division

17-VDD3.8C8DABA-17A

E.O. No. A-290-60

1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY DIESEL-STANDARD ENGINES

				Page 1 of 1		
l Corporation	Engine Fam	ily: VDD3.	8C8DABA			
232 Cubic Inc	ches					
Maximum Rated Power: 160 HP @ 3500 RPM				Engine Configuration: I-6		
Compressi	on with Glow P	lug Sp	ark			
Flex-Fuel	Dual-Fuel	Diesel X		M85		
NG LPG _	Other (spec	ify)				
282 40 CI	FR 86.1313-90	40 CFR	86.1313-94	_X_		
ass: LHD_X	MHD	HHD Ur	ban Bus	_		
TC, CAC): EC	M/PCM, CAC,	(TC),OC				
Fuel Rate	Fuel Pump		EGR	PTOX/		
@ Rated HP	& Injector	ECM/PCM	Valve	Catalytic		
mm³/Stroke	Part No.	Part No.	Part No.	Converter		
(lbs/hr)				Part No.		
8		·				
	15062018F	A281010892		25143901		
- 64.0 (74.6)	15062018F 15062019F	A281010892		25143901		
	O HP @ 3500 RP Compressi Flex-Fuel NG LPG _ 282 40 Cl lass: LHD _X TC, CAC): EC Fuel Rate @ Rated HP mm³/Stroke (lbs/hr)	232 Cubic Inches O HP @ 3500 RPM Compression with Glow P L Flex-Fuel Dual-Fuel _ NG LPG Other (spec 282 40 CFR 86.1313-90 lass: LHD _X MHD TC, CAC): ECM/PCM, CAC, Fuel Rate Fuel Pump @ Rated HP & Injector mm³/Stroke Part No. (lbs/hr)	232 Cubic Inches O HP @ 3500 RPM Compression with Glow Plug Space S	Engine Family: VDD3. 232 Cubic Inches OHP @ 3500 RPM Compression with Glow Plug Spark Engine Configuration Spark Spark Engine Configuration Spark Spark Engine Configuration Spark Spark Engine Configuration Spark Spark HO OHER 86.1313-94 Spark Spark Spark Spark Spark Spark ENGINE CONFIGURATION Spark Spark Spark		

Date Issued: 01-03-97

Rev.: