## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-27-74

Relating to Certification of New Heavy-Duty Engines and Vehicles

MACK TRUCKS, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 1998 model-year Mack Trucks, Inc. diesel-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family		Displacement (Cubic Inches)	Exhaust Emission Control Systems and Special Features
WMKXH11.9E52	11.9	(728)	Turbocharger Charge Air Cooler Engine Control Module Smoke Puff Limiter

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
1.3	15.5	4.0	0.10

The following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour, except that compliance with the carbon monoxide exhaust emission standard has been demonstrated pursuant to Title 40, Code of Federal Regulations, Part 86, Subpart A, Section 86.091-23(c)(2)(i):

Engine	Total	Nitrogen	<u>Particulates</u>
<u>Family</u>	<u>Hydrocarbons</u>	<u>Oxides</u>	
WMKXH11.9E52	0.1	3.9	0.08

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- 1. Any engine which employs a defeat device shall not be covered by this Executive Order.
- 2. Within 90 days following the issuance of this Executive Order, the manufacturer must show cause, to the satisfaction of the Executive Officer or his designee, that the strategy for fuel injection timing, including timing during the fuel economy mode, is not a defeat device.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this \_\_\_\_\_\_\_ day of January 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division

Process Code: New Submission

EPA Engine Family: WMKXH11.9E52

Manufacturer: Mack Trucks, Inc.

Manufacturer Family Name:

Family 52

7.Fuel Rate: mm/stroke@peak torque

EM,EC,TC,CAC,DI, SPL 8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930 8.Fuel Rate: 120.8 113.3 289.4 271.4 6.Torque @ RPM (SEA Gross) 1560 @ 1200 1660 @1200 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) 151.3 137.1 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) 219.0 241.7 460 @ 1800 427 @ 1800 3.BHP@RPM (SAE Gross) 2.Engine Model E7-460 E7-427 1.Engine Code N/N Ϋ́

12/12/97

EO: A-27-74