California Environmental Protection Agency		T
AIR RESOURCES BOARD	CUMMINS, INC.	EXECUTIVE ORDER A-021-0393 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE	& TEST PROCEDURE	INTENDED SERVICE CLASS ²	ECS & SPECIAL FEATURES 3
2005	5CEXH0540LAI	8.9	Diesel	Diesel	MHDD	OC, PCM, DDI, TC, CAC
ENGINE (L 8.9			ENGINE	ODELS / CODES (r	ated power, in hp}	
*			IS	SL 350 / 8780;FR91	704 (350)	······································
*	- 		·			
*	· <u> </u>			*		

nia Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; er; hp=horsepower: kw=kilowatt-

Inter in period sepured, we showed, a we showed, a set of the second sec

Lower HDD=ingn/meaium/neavy neavy-outy diesel; UB=urban ous; HDD=neavy outy Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SF/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARE=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke put| timiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; (2004may26)

of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

НСНО		РМ		co		NMHC+NOx		NOx		NMHC		
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	
EURO	FIF			15.5	15.5		•	•	•	0.5	0.5	STD
	•	0.10	0.10	13.5	+	32	3.2		*	*	*	FEL
*	*	•		4.5	26				*	0.07	0.2	CERT
•									325	0.6	ITE	
	*	• 0.09	* 0.10 0.1	* 1.5 375	2.6 19.	3.2 2.7 .0		=Federal Test	*		0.6	CERT NTE

poliphin-grains per brake horsepower-room, Financebrain test modebure, ECNO-Euro in European Steady-State Cycle, NTE-Roeno-Ecceed, STE-Statualo or emission test cap, FEL=family emission limit; CERT-certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;]

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of July 2005.

Allen Lyons, Chief Mobile Source Operations Division