Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	100			g As			ENGINE DI	ESCRIPTION			THE TOTAL OF THE PARTY OF THE P		
MANUFACTURER GENERAL MOTORS		EXECUTIVE MOD					ENGINE			NDARDS TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES	
		EXECUTIVE ORDER		R	ENGINE FAMILY		SIZES (L)			CEDURE	CLASS 2	2TWC, 2HO2S, SFI	
				_				Gasoline		Otto	HDO		
CORPORATION		A-006-1331				XH08.1503	8.1	VEHIC	E DESCR	DESCRIPTION			
Gasoline, LPG o	r Alcoh	ol Vehicles C	nly		HICL		2.50	A COMPANY OF STREET	- S. Sum Village M. W. C.		EN	GINE MODELS / CODES	
EVAPORATIVE		FUEL TANK CAPACITY			E		VEHICLE MAKE & MODELS			ENGINE (L)		(rated power, in hp)	
FAMILY	UL (K)							4500 CMC Tonkic	k C4500:			L18 / 20 (325)	
GMXE0300998	150	25, 32, 40	25, 32, 40, 57, 60, 80		2006 C4: Chevro		olet Kodiak C4500, GMC Topkick (rolet Kodiak C5500, GMC Topkick (k C5500				
GMIXEUSUUSSU		60, 8			*	00. 0	*			<u> </u>			
•						•				*			
•	*	<u> </u>								*	T *		
	•	•	*		*						†		
		+			*	I		•		L	1	ederal Regulations, Section 86.abc;	

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieur of testing. (Testing) of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

giries, are	0,00						СО			PM .	нсно		
r	NMHC		N	iOx j	NMHC+NOx				ETD	EURO	FTP	EURO	
1-			FTP	EURO	FTP	EURO	FTP	EURO	FTP	EUNO			
1	FTP	EURO	FIF	LUNG			37.1	*	•	·			
D	*	•	*			ļ		+		•	•	•	
		· -	•	•	1.0					 	•	•	
L		<u> </u>		-	0.6	•	3.4						
ERT	*							*		*		<u> </u>	
TE		*	l	•		<u> </u>				eed emission limi	· STD=standard	or emission tes	

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the Option 1 federal NMHC+NOx emission standard(s) listed above pursuant to 13 CCR 1956.1 or 13 CCR 1956.8.

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1976(b)(1)(F) {evaporative emission standards}, 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle tanks]. (The brackets [] are for gasoline, LPG or alcohol fueled vehicles only. The brackets [] are for gasoline or alcohol fueled vehicles only.)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1338 dated May 13, 2005.

Executed at El Monte, California on this ______ day of December 2005.

Allen Lyons, Chief Mobile Source Operations Division

^{*=}not applicable: GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc;

L=itler; K=1000 miles; hp=horsepower; kw=kilowatt;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=fiexible fuel;

L/M/H HDD=light/medium/heavy-duvly diesel; UB=urban bus; HDO=heavy duty Otto;

L/M/H HDD=light/medium/heavy heavy-duvly diesel; UB=urban bus; HDO=heavy duty Otto;

SCS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; RAFS/AFS=heated/air-tuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFUMFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFUMFI=sequential/multi port fuel injection; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge are cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; (2004may26) ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;