ISUZU MOTORS LIMITED

EXECUTIVE ORDER A-020-0237-1 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26. Part 5. Chapter 2: and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST PROCEDURE	SERVICE CLASS 2	ECS & SPECIAL FEATURES 3		
2007	7SZXH05.23FB	5.2	Diesel	Diesel	LHDD	DDI, TC, CAC, ECM, EGR, OC, PTOX		
ENGINE (L	_)		ENGINE M	IODELS / CODES (r	ated power, in	ı hp)		
5.2			4HK1TC / 5	23FB-1 (200), 4HK	TC / 523FB-2	2 (172)		
*				*	•			
*				•				
*	<u> </u>							

-not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; diter; hp=horsepower; kw=kilowatt;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	•	•	*		15.5	15.5	0.01	0.01	*	•
FEL.		*	1.23	1.23	1.2	1.2	•	•	•	•	*	•
CERT	0.03	0.05	1,18	1.05	1.2	1.1	0.1	0.01	0.001	0.003	*	*
NTE	0	.21	1	.84		1.8	1	9.4	0	.02		•

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed; STD=standard or emission test cap; L=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [Diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

This Executive Order hereby supersedes Executive Order A-020-0237, dated December 22, 2006.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; EBS=85% etnanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=outh fuel; DF=outh fuel; LFMHD=hight rediurn/heavy heavy-duty diesel; UBS=urban bus; HDO=heavy duty Ofto;

L/M/H HDD=hight/rediurn/heavy heavy-duty diesel; UBS=urban bus; HDO=heavy duty Ofto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DFF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throftle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; CGCARB=gaseous carburetor; IDI/DBi=indirect/direct dieses injection; TC/SC=turboyer charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=putsed/secondary air injection; SFI_moke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series

(2006DEC22)

Engine Model Summary Template

	1		i and o	C) 3,4884384	
9.Emission Control	(lbs/hr)@peak torqueDevice Per SAE J1930	DFIFER GAC	DFI,EGR,CAC,	() DELEGRAME,	TICE IN
8.Fuel Rate:	lbs/hr)@peak torque	59.5lb/hr	59.5lb/hr	45.5lb/hr	
7.Fuel Rate: mm/stroke@peak	torque	146mm^3/ST	146mm^3/ST	129.2mm^3/ST	
6.Torque @ RPM	(SEA Gross)	441lbs-ft@1850.	441lbs•ft@1850 146mm^3/ST	376lbs•ft@1600 129.2mm^3/ST	
5.Fuel Rate: (lbs/hr) @ peak HP	(for diesel only) (for diesels only) (SEA Gross)	78.5lb/l n	76.5lb/hr	69.7lb/hr	1700 - 17
Ē	(for diesel only)	子さいのテンジティ 523FA-1 4HKTTC 200HP@2400R 144.8mmA3/ST 78.5lb/lm 441lbs-ft優1850 146mm ^{A3} /ST 59.5lb/hr	R 144.8mm^3/ST	R 131.8mm^3/ST	
3.BHP@RPM	(SAE Gross)	200HP@2400	4HK1TC 200HP@2400R	4HK1TC 172HP@2400R	120000000000000000000000000000000000000
	2.Engine Model	4HK1TC	4HK1TC	4HK1TC	A CO.
	1.Engine Code	523FA-1	405.23FB 523FB-1 4HK1TC 2001	523FB-2	economy we are an experience of the control of the
	Engine Family 1.Engine Code 2.Engine Model	7.22.000.000000000000000000000000000000	75ZXH05.23FB	752XH05,23FB 523FB-2 4HK1TC	SHAND DESCRIPTION OF THE PROPERTY OF THE PROPE

- NEW RATING ADDGS VIA 12/C 06