Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY	ENGINE	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC <sup>6</sup> EMD						
YEAR	ERGINE FAMILI	SIZES (L)	· · ·	PROCEDURE	CLASS	DDI, TC, CAC, ECM, EGR, OC,							
2009	9CEXH0408BAG	6.7	Diesel	Diesel	MHDD	PTOX							
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL  ADDITIONAL IDLE EMISSIONS CONTROL													
	30g												
ENGINE (			ENGINE MO	DELS / CODES (ra	ted power, in	hp)							
6.7		See attachment for engine models and ratings											
*													
*		•											
		•											
L=liter; hip CNG/LI CNG	=horsepower, kw=kilowat; NG=compressed/liquefied no HDD=light/medium/heavy he mission control system; TW ;; DPF=diesel particulate fills e body fuel injection; SFI/MI ger, CAC=charge air cooler	hr=hour; trural gas; LPG=liquefic avy-duty diesel; UB=ur C/OC=three-way/oxidizi r; PTOX=periodic trap FI=sequential/multi port EGR / EGR-C=exhaur r; 2 (nrefix)=nrarallel:	od petroleum gas; E85=85% ban bus; HDO=heavy duty C ng cetalyst; NAC=NOx adso oxidizer; HO28/O28-heated fuel injection; DGI=direct gas st gas recirculation / cooled E (2) (suffix)=in sanes:	ethanol fuel; MF=mul bitc; rption catalyst; SCR-I l/oxygen sensor; HAF soline injection; GCAF GR; PAIR/AIR=pulse	ti fuel a.k.a. Bi J / SCR-N=sele S/AFS=heated RB=gaseous ca d/secondary air	R 86.abc=Title 40, Code of Federal Regulation ==bi fuel; DF=dual fuel; FF=flexible fuel;  ctive catalytic reduction urea / ammonia; V /air-fuel-ratio sensor (a.k.a., universal or linear or fouretor; IDI/DDI=indirect/direct diesel injection; injection; SPL=smoke puff inniter; ECM/PCM	WU (prefix) =warm oxygen sensor); n; TC/SC=turbo/ =engine/powertrair						
<sup>6</sup> ESS≔el (per 13 CC	ngine shutdown system (per R 1956 8(a)(6VD): Exempt	13 CCR 1956.8(a)(6)(A =exempted per 13 CCR	\(11\) 30a=30 a/br NOv (per 1	_NG tuel systems; N//	v=uot abbilcani	nal combustion auxiliary power system; ALT=a e (e.g., Otto engines and vehicles);	DOINGIL BAIRSILE						

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).


in g/bhp-hr	NMHC		NOx		NMHC+NOx		СО		PM		HCHO	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	0.01	0.01	*	*
FEL.	*	*	1.40	1.40	1.4	1.4	*	*	*	*	*	*
CERT	0.01	0.000	1.37	1.35	1.38	1.35	0.3	0.00	0.001	0.000	*	*
NTE	0.21		2.10		2.1		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).



**CUMMINS INC.** 

**EXECUTIVE ORDER A-021-0511 New On-Road Heavy-Duty Engines** 

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_

Annette Hebert, Chief Mobile Source Operations Division

Date: 09/23/09

## **Engine Model Summary Template**

Attachuset 1. f. 1

ಕಾರ್ಯ Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control PeDevice Per SAE J1930
edExH0408BAG	3381;FR93118	ISB 300/PX6	300@2564	127	110	620@1600	123	66.2	RTOX, PCM,
≭CE≾FÐ408BAG	3382;FR93125	ISB 280/PX6	280@2500	123	104	660@1600	129	69.7	PTOX, P¢M,
DOFKH0408BAG	3381;FR93119	ISB 260/PX6	280@2500	123	104	660@1600	129	69.7	РТОХ, РСМ,
⊮CLXH0408BAG	3388;FR93126	ISB 240/PX6	260@2500	114	96.3	620@1600	121	65.4	РТОХ√РСМ,
)	3389;FR93120	ISB 280/PX6	260@2500	114	96.3	620@1600	121	65.4	ртох,∕рсм,
∘0E.≮H0408BAG	3388;FR93129	ISB 260/PX6	240@2500	108	90.9	620@1600	121	65.4	ртох, Рсм,
MCEAH0408BAG	3389:FR93121	ISB 240/PX6	240@2500	108	90.9	620@1600	121	65.4	РТОХ, РСМ,
₩CEXH0408BAG	3388;FR93130	ISB 240/PX6	240@2500	108	90.9	560@1600	109	58.8	РТОХ, РСМ,
HELATH408BAG	3389;FR93122	ISB 240/PX6	240@2500	108	90.9	560@1600	109	58.8	PTOX, PCM,
HOLXH0408BAG	3389;FR93123	ISB 220/PX6	220@2500	97	82.0	520@1600	103	55.5	PTOX, PCM,
BOEXH0408BAG	3389;FR93124	IS8 200/PX6	200@2400	97	78.5	520@1600	103	55.5	F(TOX, PCM, '

OC DAT, TC ECM,