

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	MODEL ENGINE FAMILY 2011 BCEXH0408BAH		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
			6.7	Diesel	PROCEDURE	CLASS MHDD	DDI, TC, CAC, ECM, EGR, OC, PTOX, SCR-U	EMD				
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL			ADDITIONAL IDLE EMISSIONS CONTROL 5									
	30g				N/	Ά						
ENGINE (L)			ENGINE MODELS / CODES (rated power, in hp)									
6.7	6.7 See attachment for engine models and ratings											
L=liter; hp:	* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;											
L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) = warm-up catalyst; DPF=diesel particulate filter, PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SPIMFI=sequential/multi-port fuel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; ESS=content by the fuel of the content												
(per 13 CCI	ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);											

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		co		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	0.33	0.33	*	*	*	*	*	*	*	*
CERT	0.01	0.001	0.17	0.18	*	*	0.00	0.00	0.000	0.000	*	*
NTE	0.21		0.50		*		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour, FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 27, 2010, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: That the manufacturer has elected to include engine models in this engine family which are identified for "emergency vehicle use only". These "emergency vehicle use only" engines are exempt from requirements imposed pursuant to California law and the regulations adopted pursuant thereto for motor vehicle pollution control devices per California Vehicle Code Section 27156.2. The manufacturer must clearly label these engines for "emergency vehicle use only" on the engines' emission control label.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971 (engine manufacturer diagnostic) and 13 CCR 2035 et seq. (emission control warranty).

Engine Model Summary Template

A-021-0550-1

A Hackment: page 10/2

	12-31-	2012	2 0410 @ 0014	4.Fuel Rate:	5.Fuel Rate:	6 Tarries & DDM	7.Fuel Rate:	9 Eugl Date:	O Francisco Control
Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	mm/stroke @ peak HP (for diesel only)	(lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control PDevice Per SAE J1930
BCEXH0408BAH	3072;FR92508	ISB6.7 360	360@2600	150	132	800@1800	158	96	SCRC, PTOX
BCEXH0408BAH	3072;FR92507	ISB6.7 340	340@2800	134	127	660@1600	127	68	SCRC, PTOX,
BCEXH0408BAH	3335;FR92498	ISB6.7 250	245@2600	122	107	660@1600	133	72	SCRC, PTOK,
BCEXH0408BAH	3335;FR92496	ISB6.7 240	235@2600	116	102	560@1600	116	63	SCRC, PTOX,
BCEXH0408BAH	3336;FR92687	ISB6.7 300	300@2600	139	122	660@1600	132	71	SCRC, PTOX,
BCEXH0408BAH	3336;FR92504	ISB6.7 280	270@2600	128	113	660@1600	133	72	SCRC, PTQX,
BCEXH0408BAH	3336;FR92501	ISB6.7 260	250@2600	123	108	660@1600	133	72	SCRC, PTOX,
BCEXH0408BAH	3336;FR92499	ISB6.7 250	245@2600	122	107	660@1600	133	72	SCRC, PTOX,
BCEXH0408BAH	3336;FR92497	ISB6.7 240	235@2600	116	102	560@1600	116	63	SCRC, PTOX,
BCEXH0408BAH	3070;FR92495	ISB6.7 220	215@2600	94	83	520@1600	103	55	scrd, ptox,
BCEXH0408BAH	3070;FR92494	ISB6.7 200	195@2600	97	85	520@1600	108	58	SCRC Prox,
BCEXH0408BAH	3071;FR92686	ISB6.7 220	215@2600	94	83	520@1600	103	55	SCRC, PTOX,
BCEXH0408BAH	3071;FR92685	ISB6.7 200	195@2600	97	85	520@1600	108	58	SCRC, TOX,
BCEXH0408BAH	3072;FR92508	PX6 360	360@2600	150	132	800@1800	158	96	SCRC, TOX,
BCEXH0408BAH	3072;FR92507	PX6 340	340@2800	134	127	660@1600	127	68	SCRC, TOX,
BCEXH0408BAH	3335;FR92498	PX6 250	245@2600	122	107	660@1600	133	72	SCRC, PTOX,
BCEXH0408BAH	3335;FR92496	PX6 240	235@2600	116	102	560@1600	116	63	SCRC/PTOX,
BCEXH0408BAH	3336;FR92687	PX6 300	300@2600	139	122	660@1600	132	71	SCRC PTOX,
BCEXH0408BAH	3336;FR92504	PX6 280	270@2600	128	113	660@1600	133	72	scrd, Ptox,
BCEXH0408BAH	3336;FR92501	PX6 260	250@2600	123	108	660@1600	133	72	SCR¢, PTOX,
BCEXH0408BAH	3336;FR92499	PX6 250	245@2600	122	107	660@1600	133	72	SCRC, PTOX,
BCEXH0408BAH	3336;FR92497	PX6 240	235@2600	116	102	560@1600	116	63	SCRC, PTOX,
BCEXH0408BAH	3070;FR92495	PX6 220	215@2600	94	83	520@1600	103	55	SCRC, PTOX,
BCEXH0408BAH	3070;FR92494	PX6 200	195@2600	97	85	520@1600	108	58	SCRC, PTOX,
BCEXH0408BAH	3071;FR92686	PX6 220	215@2600	94	83	520@1600	103	55	SCRC, PTOX,
BCEXH0408BAH	3071;FR92685	PX6 200	195@2600	97	85	520@1600	108	58	SCRC, PTOX,
BCEXH0408BAH	3727;FR93533	ISB6.7 280	270@2600	128	113	660@1600	133	72	SCRC, PTDX,
BCEXH0408BAH	3072;FR92506	ISB6.7 325	315@2600	141	124	750@1800	149	91	SCRC, PTOX,
						((SCR-U.P7	ox, CAC TC.	ECM, OC, DOILEGER

Engine Model Summary Template

A-021-0550-1

A Hanher: page 20/2

12 -	31-2012		4 DUD @ DD14	4.Fuel Rate:	5.Fuel Rate:	C Tarrico & DDM	7.Fuel Rate:	8.Fuel Rate:	9.Emission Control
Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	mm/stroke @ peak HP (for diesel only)	(lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	mm/stroke@peak torque		Device Per SAE J1930
BCEXH0408BAH	3432;FR93187	ISB6.7 360	360@2600	150	132	800@1800	158	96	SCRC, PTOX,
BCEXH0408BAH	3432;FR93186	ISB6.7 340	340@2800	134	127	660@1600	127	68	SCRC, PTOX,
BCEXH0408BAH	3335;FR92505	ISB6.7 300	300@2600	139	122	660@1600	132	71.	SCRC, PTOK,
BCEXH0408BAH	3335;FR92503	ISB6.7 280	270@2600	128	113	660@1600	133	72	SCRC, PTCX,
BCEXH0408BAH	3335;FR92500	ISB6.7 260	250@2600	123	108	660@1600	133	72	SCRC, PTCX,
BCEXH0408BAH	3072;FR92506	PX6 325	315@2600	141	124	750@1800	149	91	SCRC, PTOX,
BCEXH0408BAH	3432;FR93187	PX6 360	360@2600	150	132	800@1800	158	96	SCRC, PTOX,
BCEXH0408BAH	3432;FR93186	PX6 340	340@2800	134	127	660@1600	127	68	SCRC, PTØX,
BCEXH0408BAH	3335;FR92505	PX6 300	300@2600	139	122	660@1600	132	71	SCRO PTOX,
BCEXH0408BAH	3335;FR92503	PX6 280	270@2600	128	113	660@1600	133	72	SCRC, PTOX,
BCEXH0408BAH	3335;FR92500	PX6 260	250@2600	123	108	660@1600	133	72	SCRC, PTOX,
		Make year highway and Alexander and Alexander and Alexander	en estas construitos estas con construitores entre con con-	ong til som kall sig still og til flestiger og til til som til skal som kladet som		aldessäller (mann a krit – konst fällssäll monrakt at för minna (k. s. 1 och skonste)	r syggen gan nystyrthau men seithelich derson eintheuns ein nach hab ha	eli man e dialektora un'algora manus minambe un como minambe	e end in the course of the community of the second
Emergency	Vehicle	Engine	Models	Below	The substitution of the second state of the second state of the second state of the second state of the second	dans, inc., national approximation of the communities with the	and the state of t	o como en como en apartega en relega e de Preside, e que estrativo	
BCEXH0408BAH	3072;FR92506	ISB6.7 325	315@2600	141	124	750@1800	149	91	SCRC, PTOX,
BCEXH0408BAH	3432;FR93187	ISB6.7 360	360@2600	150	132	800@1800	158	. 96	SCRC, PTOX,
BCEXH0408BAH	3432;FR93186	ISB6.7 340	340@2800	134	127	660@1600	127	68	SCRC, PTOX,
BCEXH0408BAH	3335;FR92505	ISB6.7 300	300@2600	139	122	660@1600	132	. 71	SCRC, PTOX,
BCEXH0408BAH	3335;FR92503	ISB6.7 280	270@2600	128	113	660@1600	133	72	SCRC, PTOX,
BCEXH0408BAH	3335;FR92500	ISB6.7 260	250@2600	123	108	660@1600	133	72	SCRC PTOX,
BCEXH0408BAH	3072;FR92506	PX6 325	315@2600	141	124	750@1800	149	91	SCRO, PTOX,
BCEXH0408BAH	3432;FR93187	PX6 360	360@2600	150	132	800@1800	158	96	scrc, $ptdx$,
BCEXH0408BAH	3432;FR93186	PX6 340	340@2800	134	127	660@1600	127	68	SCRC, PTDX,
BCEXH0408BAH	3335;FR92505	PX6 300	300@2600	139	122	660@1600	132	71	SCRC, PTOX,
BCEXH0408BAH	3335;FR92503	PX6 280	270@2600	128	113	660@1600	133	72	SCRC, PTOX,
BCEXH0408BAH	3335;FR92500	PX6 260	250@2600	123	108	660@1600	133	· 72	SCRC, PTOK,
							Can		

SCR-U, PTOX, CAC, TC, FOM, OC, DDT, EGA