

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-75
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1985 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for gasoline-powered light-duty trucks:

<u>Engine Family</u>	<u>Displacement Cubic Inches (Liters)</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
FTY2.0T5FBB3	121.9 (2.0)	Exhaust Gas Recirculation Three-Way Catalyst with Closed Loop (Electronic Fuel Injection)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the certification emission standards for this engine family to be listed on the window decal required by "California Assembly-Line Test Procedures for 1983 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles":

<u>Equivalent Inertia Weight</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0-3999	0.39	9.0	1.0

The following are the certification emission values for the above engine family:

<u>Equivalent Inertia Weight</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0-3999	0.24	2.2	0.2

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.15 of Title 13, California Administrative Code which includes repair or replacement of emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 31st day of August, 1984.

Bob Cross for

K. D. Drachand, Chief
Mobile Source Division

17.10.00 Supplemental data sheets

1985 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Page 1

Manufacturer Toyota Motor Corporation

Executive Order No. A-14-75

Engine Family FTY2.0T5FBB3

Evaporative Family EV-E

Engine CID (Liters) 121.9 (2.0)

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance

EEC-Electronic Engine Control

EI-Electronic Ignition

ESAC-Electronic Spark Advance
Control

VA-Vacuum Advance

VR-Vacuum Retard

Exhaust Emissions Control System

AIP-Air Injection-Pump

AIV-Air Injection-Valve

CL-Closed Loop

EGR-Exhaust Gas Recirculation

EM-Engine Modification

OC-Oxidation Catalyst System

TOC-Trap Oxidizer Continual

TOP-Trap Oxidizer Periodical

TR-Thermal Reactor

TWC-Three Way Catalyst System

Special Features

CCV-Combustion

Chamber Valve

CFI-Central Fuel
Injection

DID-Diesel

Injection-

Direct

DIP-Diesel

Injection-

Prechamber

EFI-Electronic

Fuel Injection

IC-Intercooler

MFI-Mechanical

Fuel Injection

TC-Turbocharged

Fuel System

CFI, CL, DID, DIP, EFI, MFI

nV-nVenturi Carburetor

W-Variable Venturi

VEHICLE MODELS :

YR21LG-MDEA }
-MQEA }
-PDEA }
-PQEA } *Van*
YR27LV-MREA } *cargo Van*
-PREA }

DRIVE SYSTEM : Front Engine/Rear - Wheel Drive

E.O. #A ~14-75

1985 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

 Passenger Cars x Light-Duty Trucks Medium-Duty Vehicles x Gas DieselManufacturer Toyota Motor Corporation Page 2Engine Family FTY2.0T5FEB3 Engine Code 1 thru 8CID (Liter)- 121.9(2.0)ECS (Special Features) CL + EGR + TWC (EFI) Type 4 cyl. in-line

Engine code	Vehicle Models (If Coded see attachment) Refer to 08.13.03.00	Trans.	Equiv. Test Weight	Ign. System CA, EI, VA Part No. [Distribu- tor]	Fuel System CL, EFI Part No. [Computer] [Air flow meter] [Injector]	EGR Valve Part No.	Label Ident. Part No.
1 thru 4	YR21LG-MDEA -MQEA YR27LV-MREA	M5	3,125 3,250 3,375 3,500	19030-73020	89561-28010 22250-73010 23250-45011	25620-73010	11298-73032
5 thru 8	YR21LG-PDEA -PQEA YR27LV-PREA	A4	3,250 3,375 3,500				

Comments : See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

*Add 10% to dyno test HP for air conditioning usage.