State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-86 Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1986 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for gasoline-powered light-duty trucks:

Engine Family	Displacement <u>Cubic Inches (Liters)</u>		Exhaust Emission Control Systems (Special Features)		
GTY2.4T2FCC8	144.4	(2.4)	Air Injection-Valve Exhaust Gas Recirculation Three-Way Catalyst with Closed Loop		

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Equivalent Inertia Weight	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per Mile	Nitrogen Oxides Grams per mile	
0-3999	0.39	9.0	1 . 0	

The following are the certification emission values for this engine family:

Equivalent Inertia Hydrocarbons Weight Grams per Mile		Carbon Monoxide Grams per Mile	Nitrogen Oxides Grams per Mile	
0-3999	0.19	5.8	0.5	

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 26 H day of July, 1985.

K. D. Drachand, Chief Mobile Source Division

3	1986 AIR RESO	URCES B	OARD SUPPLEMENTAL DATA SHEET	İ
				Page 1
Manufacturer Toyota Motor Corporation			Executive Order No. A-1	1-86
<i>-</i>	GTY2.4T2FCC8		Evaporative Family	V-R
			Engine CID (Liters) 14	14.4 (2.4)
ABBREVIATIONS			•	
Ignition System		<u> Esha</u>	ust Emissions Control System	Special Peatures
CA-Centrifugal A	dvance	AIP-	Air Injection-Pump	CCV-Combustion
ERC-Electronic E	ngine Control	AIV-	Air Injection-Valve	Chamber Valve
EI-Electronic Ig	nition	CI-C	losed Loop	CPI-Central Fuel
ESAC-Electronic	Spark Advance	BGR-	Exhaust Gas Recirculation	Injection
Control		PH-E	ngine Modification	DID-Diesel
VA-Vacuum Advance	e	oc-o	kidation Catalyst System	Injection-
VR-Vacuum Retard		10C-	Trap Oxidizer Continual	Direct
		105~	Trap Oxidizer Periodical	DIP-Diesel
		TR-T	hermal Reactor	Injection-
•		TWC-	Three Way Catalyst System	Prechamber
el System				EFI-Electronic
CTI, CL, DID, DI	P, EFI, MFI			Fuel Injection
nV-nVenturi Carb	uretor			IC-Intercooler
W-Variable Venturi				MFI-Mechanical
				Fuel Injection
				TC-Turbocharged
			*	

VEHICLE MODELS :

Truck 2WD	Truck 2WD	Truck 2WD	Truck 4WD
RNSOL-KRA	RN55L-MRA	RN70L-MDCA	RN61L-MRA
-MRA	-MOA	-SDCA	rn66l-mda
-SRA	-SRA		-MDCA
	-974		

DRIVE SYSTEM: RN50L, RN55L, RN70L series; Front Engine/Rear - Wheel Drive RN61L, RN66L series; Front Engine/4 - Wheel Drive

Page : 17-81

Issued: 06/05/85 Rev. 1: 07/1/85

E.O. #A	14-86	
---------	-------	--

1986 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passen	ger Cars <u>x</u> Li	ght-Dut	y Truck	s <u> </u>	m-Duty Vehic	les <u>x</u> Gas	Diesel
Manufactur	er Toyo	ta Moto	r Corpo	ration	Page	2	<u> </u>
	aily GTY2				Engin Code	e l thr	
ECS (Speci	al Features)	AIV +	CL + B	GR + TWC	Type	144.4(2.4) 4 cyl. in-	line
		T		T	T		
Engine code	(If Coded see attachment) Refer to	Trans.	Test	[Distribu-	CL, 2V Part No.		Label Ident
	08.13.03.00			tor]	tor]		
1, 2	RN50L-KRA	M4	2,750 2,875	19100-35150	21100-35310	25620-35120	11298-35810
	RN50IL-MRA RN55IL-MRA -NDA RN70IL-MDCA	M5	2,875 3,000	,	·		
i	RN61L-MRA RN66L-MDA -MDCA	MS	3,500				
3, 4,	RN50L-SRA RN55L-SRA -SDA RN70L-SDCA	M	2,875 3,000		21100-35390		

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

*Add 10% to dyno test HP for air conditioning usage.

Page : 17-82

Issued: 06/05/85